

Cable hanger, non-insulated, bolt-on, for 7/8" coaxial cable and E100, E105 elliptical waveguide

Hanger, non-insulated, bolt-on for coaxial cable LCF78 / UCF78 / RCF78 / HCA78 and for eliptical waveguide EP100/E105/EP105 made of stainless steel

FEATURES / BENEFITS

Stainless steel hangers for supporting elliptical waveguide to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



ı	External Document Links	Notes
ı	Technical features	
ı		
ı	GENERAL SPECIFICATIONS	
н		

Product Line		Coaxial Cable Accessories Radiating Cable Accessories Elliptical Waveguide Accessories Hybrid Cable Accessories
Product Type		Hanger
Hanger Type		Bolt-On, non-insulated
Transmission Line Type		LCF78 UCF78 RCF78 EP100 E105 EP105 HB078 HCA78
Cable Type		Coaxial Foam Dielectric Radiating Cable Hybrid
MECHANICAL SPECIFICATIONS		
Cable Size		7/8
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
TEMPERATURE SPECIFICATIONS		
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)
PACKAGING INFORMATION		
Package Quantity		10

CLAMP-105 REV : E REV DATE : 13 Jul 2023 **www.rfsworld.com**