



# RADIO FREQUENCY SYSTEMS

## RF CABLE SOLUTIONS SELECTION GUIDE

Edition 1 / 7.2022





## RADIO FREQUENCY SYSTEMS

### TABLE OF CONTENTS

<b>CELLFLEX® COAXIAL CABLES</b> CELLFLEX sets the standard for <b>communication cables</b>	2
<b>STANDARD AND PREMIUM CONNECTORS</b> OMNI FIT connectors <b>for every application and budget</b>	4
<b>KITTING SOLUTIONS</b> CELLFLEX MultiFlex <b>all-in-one pre-assembled solutions</b> save time & effort	5
<b>CELLFLEX® TECHNICAL INFORMATION</b> Cable, connector and accessory <b>data specifications</b>	6
<b>CLEARFILL® LINE PLENUM-RATED CABLES</b> Air-dielectric coaxial cables that operate in frequencies from 380 MHz <b>to 6 GHz</b>	16
<b>RF JUMPER CABLES</b> High-performance jumper cables <b>for any application, any size</b>	18
<b>ADAPTER SERIES</b> Easy field <b>connections</b>	21
<b>CELLFLEX® CABLE MODEL STRUCTURES</b> Understanding <b>RFS model numbers</b>	22
<b>JUMPER MODEL STRUCTURES</b> Understanding <b>RFS model numbers</b>	23

## CELLFLEX® SETS THE STANDARD FOR COMMUNICATION CABLES

It was 1961 when we pioneered CELLFLEX, the foam dielectric corrugated coaxial cables that quickly became the industry's preferred choice for base station applications. Since then, CELLFLEX cables have been proving their value in indoor and outdoor applications around the world.



Today, our premium attenuation, low-loss CELLFLEX cables continue to set industry standards for performance, flexibility and durability.

### INDUSTRY-LEADING ELECTRICAL PERFORMANCE

CELLFLEX foam dielectric corrugated cables feature copper outer and inner conductors that are key to improving performance:

- The two, solid copper conductors virtually eliminate interference due to passive intermodulation (PIM) and intermodulation distortion (IMD).
- The outer conductor creates a continuous electromagnetic and radio frequency interference (EMI/RFI) shield that minimizes system interference.

With extremely low attenuation, excellent heat transfer properties and temperature-stabilized dielectric material, CELLFLEX cables deliver safe, long-term operation, even at high transmit power levels. Special low VSWR cable models help maintain system integrity.

### REMARKABLE FLEXIBILITY AND STRENGTH

We've been continually advancing and refining our corrugation technology since we invented the first corrugated, seam-welded cable in 1951. Our ongoing dedication to superior corrugation techniques means CELLFLEX cables bend easily without risk of damage, even against strong bending forces. This rugged flexibility makes installations faster, easier and lower risk than installations using smooth wall cables.

CELLFLEX cables are also easier to reuse and recycle than competing cables because the layers are not bonded.



## CELLFLEX® SETS THE STANDARD FOR COMMUNICATION CABLES

### A COMPREHENSIVE, FUTUREPROOF PORTFOLIO

Our entire portfolio of CELLFLEX cables supports frequencies from low MHz ranges to 6 GHz to protect your investment. You can take advantage of emerging spectrum and evolve to 5G anywhere in the world — no matter which stage of evolution you're in today.


With 20 CELLFLEX cable models ranging from 1/4-inch to 1 5/8-inch in diameter, there's a CELLFLEX cable for even the most complicated and demanding applications.

Together, CELLFLEX and CELLFLEX Lite make up the largest corrugated transmission-line portfolio in the wireless infrastructure industry.

### MEETING THE WORLD'S HIGHEST FIRE SAFETY STANDARDS

CELLFLEX cables have achieved the top Construction Products Regulation (CPR) rating of B2ca with a d0 droplets rating. They also meet international flame- and fire-retardancy standards, including:

- IEC 60754-1/-2: Halogen-free and non-corrosive jacket tests
- IEC 60332-1: Flame tests
- IEC 60332-3-24: Cable bundle tests
- IEC 61034: Low-smoke emission tests



## CELLFLEX® LITE

### Reduce your reliance on copper cables

When we invented CELLFLEX Lite foam dielectric corrugated coaxial cables in 2006, they were the first in the industry to combine an aluminum outer conductor with a copper inner conductor.

These lightweight cables are the ideal alternative to CELLFLEX copper cables when fluctuating copper prices rise and in areas

where copper theft is an issue. They're easy to transport, handle and install. And they offer an unbeatable price-performance combination.

CELLFLEX Lite communications cables deliver world-class electrical performance that meets or exceeds that of many other vendors' copper cables.

## OMNI FIT™ CONNECTORS FOR EVERY APPLICATION AND BUDGET

OMNI FIT connectors are known throughout the industry for their precision-engineered performance, ease of installation and long life in the field. They can be used with copper and aluminum cables, and are the perfect complement to our CELLFLEX® and CELLFLEX Lite communications cables in any scenario:

- Tower and rooftop deployments
- Small cell deployments in dense urban environments
- Indoor and underground deployments

### A COMPLETE PORTFOLIO TO CHOOSE FROM

Simply choose the OMNI FIT connectors that match your requirements:

**OMNI FIT Premium** E01 series connectors are fully optimized to deliver the ultimate combination of electrical performance, simplicity, durability and cost.

**OMNI FIT Standard** C03 series connectors deliver a first-class feature set at a very cost-effective price point.

Our complete portfolio of OMNI FIT Premium and OMNI FIT Standard connectors is available with spacing-saving 4.3-10 interfaces as well as traditional Type-N and 7-16 DIN interfaces in all interface combinations, versions and variants.

### DESIGNED FOR FUTUREPROOF EVOLUTION TO 5G

OMNI FIT connectors support all frequencies up to 6 GHz, making them the perfect choice for smooth evolution to 5G globally.

You can take advantage of newly available spectrum such as Citizens Broadband Radio Service (CBRS), C-Band and License Assisted Access (LAA) today, then seamlessly switch to different frequencies tomorrow.

### IDEAL FOR RETROFITS AND UPGRADES

Because OMNI FIT connectors are backwards compatible with so many installed cables, they're a very cost-effective way to instantly gain access to the fully frequency range supported by existing cables.

Simply replace legacy, frequency-limited connectors with OMNI FIT connectors to extend the life of current installations, reduce upgrade costs and gain higher returns on previous investments.



## OMNI FIT™ CONNECTORS FOR EVERY APPLICATION AND BUDGET

### OMNI FIT PREMIUM: MAXIMUM VALUE FOR THE PRICE

OMNI FIT Premium connectors are tested and proven to deliver outstanding PIM and VSWR performance at all frequencies up to 6 GHz. They feature an ultra-compact, lightweight and extremely robust two-piece design that simplifies installations and avoids the need for additional parts that can complicate installations or be lost.

To ensure watertight durability, OMNI FIT Premium E01 series connectors include a built-in seal against the outer conductor and against the cable jacket so there's no need for external sealing. They can be installed using the same tools and following the same principles as the previous generation D01 connectors.

### OMNI FIT STANDARD: COST-EFFECTIVE CONNECTORS WITH NO COMPROMISES

OMNI FIT Standard connectors provide key performance and design features that help you squeeze every last bit of performance out of infrastructure at a very appealing price point.

The high-performance C03 series connectors provide excellent PIM and VSWR ratings that help to maintain signal quality and system performance end-to-end. They also feature a lightweight design that simplifies installation and minimizes weight burdens.

With three attachment options to choose from — push-pull, hand-screw and hex-head — OMNI FIT Standard connectors are easy to install in any environment.



## CELLFLEX® MULTIFLEX ALL-IN-ONE SOLUTION

Accelerate Installations



CELLFLEX MultiFlex cabling solutions feature 1-meter (3-ft) CELLFLEX jumpers connected to each end of a CELLFLEX feeder cable of any length with OMNI FIT™ connectors. You choose the jumper, cable and connector combination you need, and we take care of assembly.

With a pre-assembled CELLFLEX MultiFlex solution, you'll save time and effort across indoor and

outdoor installations. And you'll have the ultimate combination: The flexibility of jumpers, the outstanding performance of larger feeder cables and the reliability of factory-installed connectors.

All CELLFLEX MultiFlex solutions support frequencies up to 6 GHz to get you to 5G faster anywhere in the world.



## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**SCF14 Series: 20.4 GHz**

### ORDERING INFORMATION

Jacketing Options	Standard Attenuation Cable Model Numbers
Outdoor standard:	<a href="#">SCF14-50J</a>
Indoor flame retardant:	<a href="#">SCF14-50JFN</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS		
Dimensions Over Jacket	mm (in)	7.8 (0.307)
Min. Bending Radius, Repeated	mm (in)	25 (0.984)
Jacket Type		Polyethylene, PE
Bending Moment	Nm (lb-ft)	0.7 (0.5)
Tensile Strength	N (lb)	600 (135)
Recommended/Maximum Clamp Spacing	m (ft)	0.2 / 0.2 (0.67 / 0.67)

TEMPERATURE SPECIFICATIONS		
Installation	°C (°F)	-40 to 60 (-40 to 140)
Installation - JFNA	°C (°F)	-25 to 60 (-13 to 140)
Storage	°C (°F)	-70 to 85 (-94 to 185)
Operation	°C (°F)	-50 to 85 (-58 to 185)

ELECTRICAL SPECIFICATIONS		
Operating Frequency Band	GHz	20.4
Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222) Premium 23 (1.152) Premium 24 (1.135)

ATTENUATION			
Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW
800	17.30	5.27	0.38
1800	26.90	8.20	0.25
2400	31.30	9.60	0.21
3500	39.10	11.90	0.17
5000	48.00	14.60	0.14
6000	53.40	16.30	0.12
8000	63.40	19.30	0.10
10000	72.60	22.10	0.09
12000	81.00	24.80	0.08
16000	97.00	29.60	0.07
18000	105.00	31.90	0.06
20400	113.00	34.60	0.06

### RELATED PRODUCTS

Premium Connector Series E01	
Model Number	Type
<a href="#">716M-SCF14-E01</a>	7-16 Male
<a href="#">NM-SCF14-E01</a>	N Type Male
<a href="#">NF-SCF14-E01</a>	N Type Female
<a href="#">43MR-SCF14-E01</a>	4.3-10 Male Right Angle
<a href="#">43M-SCF14-E01</a>	4.3-10 Male
Tools for Series E01	
<a href="#">TRIM-SET-S14-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IS14-D01</a>	Univ. Trimming Tool Insert

Accessories	
Model Number	Type
<a href="#">TRIM-T01</a>	Hand Tool Kit

## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**SCF38 Series: 13.4 GHz**

### ORDERING INFORMATION

Jacketing Options	Standard Attenuation Cable Model Numbers
Outdoor standard:	<a href="#">SCF38-50J</a>
Indoor flame retardant:	<a href="#">SCF38-50JFN</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS		
Dimensions Over Jacket	mm (in)	10.2 (0.402)
Min. Bending Radius, Repeated	mm (in)	25 (0.984)
Jacket Type		Polyethylene, PE
Bending Moment	Nm (lb-ft)	1.4 (1)
Tensile Strength	N (lb)	600 (135)
Recommended/Maximum Clamp Spacing	m (ft)	0.25 / 0.25 (0.8 / 0.8)

TEMPERATURE SPECIFICATIONS		
Installation	°C (°F)	-40 to 60 (-40 to 140)
Installation - JFNA	°C (°F)	-25 to 60 (-13 to 140)
Storage	°C (°F)	-70 to 85 (-94 to 185)
Operation	°C (°F)	-50 to 85 (-58 to 185)

ELECTRICAL SPECIFICATIONS		
Operating Frequency Band	GHz	13.4
Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222) Premium 23 (1.152) Premium 24 (1.135)

ATTENUATION			
Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW
800	12.73	3.88	0.62
1800	20.05	6.11	0.39
2400	23.70	7.21	0.33
3500	29.50	9.01	0.27
5000	36.60	11.16	0.22
6000	41.00	12.48	0.19
8000	49.00	14.94	0.16
10000	56.50	17.21	0.14
12000	63.50	19.37	0.12
13400	68.30	20.82	0.12

### RELATED PRODUCTS

Premium Connector Series E01	
Model Number	Type
<a href="#">NM-SCF38-E01</a>	N Type Male
<a href="#">NF-SCF38-E01</a>	N Type Female
<a href="#">43M-SCF38-E01</a>	4.3-10 Male
Tools for Series E01	
<a href="#">TRIM-SET-S38-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IS38-D01</a>	Univ. Trimming Tool Insert

Accessories	
Model Number	Type
<a href="#">RSB-S38/L14</a>	Stainless Steel Clamp
<a href="#">TRIM-T01</a>	Hand Tool Kit

## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**SCF12 Series: 10.6 GHz**

### ORDERING INFORMATION

Jacketing Options	Standard Attenuation Cable Model Numbers
Outdoor standard:	<a href="#">SCF12-50J</a>
Indoor flame retardant:	<a href="#">SCF12-50JFN</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS			ELECTRICAL SPECIFICATIONS			
Dimensions Over Jacket	mm (in)	13.7 (0.539)	Operating Frequency Band	GHz	10.6	
Min. Bending Radius, Repeated	mm (in)	32 (1.3)	Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222) Premium 23 (1.152) Premium 24 (1.135)	
Jacket Type		Polyethylene, PE	<b>ATTENUATION</b>			
Bending Moment	Nm (lb-ft)	2.5 (1.84)	Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW
Tensile Strength	N (lb)	650 (146)	800	9.57	2.92	0.74
Recommended/Maximum Clamp Spacing	m (ft)	0.3 / 0.5 (1 / 1.64)	1800	14.90	4.55	0.47
<b>TEMPERATURE SPECIFICATIONS</b>			2400	17.50	5.35	0.40
Installation	°C (°F)	-40 to 60 (-40 to 140)	3500	21.80	6.63	0.32
Installation - JFNA	°C (°F)	-25 to 60 (-13 to 140)	5000	26.80	8.16	0.26
Storage	°C (°F)	-70 to 85 (-94 to 185)	6000	29.80	9.09	0.24
Operation	°C (°F)	-50 to 85 (-58 to 185)	8000	35.50	10.80	0.20
			10000	40.60	12.40	0.17

### RELATED PRODUCTS

#### Standard Connectors

Model Number	Type
<a href="#">716M-SCF12-C03</a>	7-16 Male
<a href="#">716F-SCF12-C03</a>	7-16 Female
<a href="#">43M-SCF12-C03</a>	4.3-10 Male
<a href="#">43MH-SCF12-C03</a>	4.3-10 Male, Hand Screw
<a href="#">43MP-SCF12-C03</a>	4.3-10 Male, Push-Pull
<a href="#">43F-SCF12-C03</a>	4.3-10 Female
<a href="#">NM-SCF12-C03</a>	N Type Male
<a href="#">NF-SCF12-C03</a>	N Type Female
<a href="#">716MR-SCF12-C03</a>	7-16 Male Right Angle
<a href="#">43MR-SCF12-C03</a>	4.3-10 Male Right Angle

#### Tools for Series C03

<a href="#">TRIM-SET-S12-C02</a>	Universal Trimming Tool
----------------------------------	-------------------------

#### Premium Connector Series E01

Model Number	Type
<a href="#">716M-SCF12-E01</a>	7-16 Male
<a href="#">716F-SCF12-E01</a>	7-16 Female
<a href="#">43M-SCF12-E01</a>	4.3-10 Male
<a href="#">43F-SCF12-E01</a>	4.3-10 Female
<a href="#">NM-SCF12-E01</a>	N Type Male
<a href="#">NF-SCF12-E01</a>	N Type Female
<a href="#">716MR-SCF12-E01</a>	7-16 Male Right Angle
<a href="#">43MR-SCF12-E01</a>	4.3-10 Male Right Angle
<a href="#">NMR-SCF12-E01</a>	N Type Male Right Angle

#### Tools for Series E01

<a href="#">TRIM-SET-S12-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IS12-D01</a>	Univ. Trimming Tool Insert

#### Accessories

Model Number	Type
<a href="#">RSB-S12</a>	Stainless Steel Clamp
<a href="#">RSB-S12/78</a>	Stainless Steel Clamp
<a href="#">TRIM-T01</a>	Hand Tool Kit

## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**LCF14 Series: 15.8 GHz**

### ORDERING INFORMATION

Jacketing Options	Standard Attenuation Cable Model Numbers
Outdoor standard:	<a href="#">LCF14-50J</a>
Indoor flame retardant:	<a href="#">LCF14-50JFN</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS			ELECTRICAL SPECIFICATIONS			
Dimensions Over Jacket	mm (in)	10 (0.394)	Operating Frequency Band	GHz	15.8	
Min. Bending Radius, Single	mm (in)	40 (1.575)	Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222) Premium 23 (1.152) Premium 24 (1.135)	
Min. Bending Radius, Repeated	mm (in)	85 (3.346)	<b>ATTENUATION</b>			
Jacket Type		Polyethylene, PE	Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW
Bending Moment	Nm (lb-ft)	1.9 (1.4)	800	12.40	3.77	0.59
Tensile Strength	N (lb)	890 (200)	1800	19.10	5.82	0.38
Recommended/Maximum Clamp Spacing	m (ft)	0.5 / 1 (1.75 / 3.25)	2400	22.30	6.81	0.33
<b>TEMPERATURE SPECIFICATIONS</b>			3500	27.50	8.39	0.27
Installation	°C (°F)	-40 to 60 (-40 to 140)	5000	33.70	10.30	0.22
Installation - JFNA	°C (°F)	-25 to 60 (-13 to 140)	6000	37.40	11.40	0.20
Storage	°C (°F)	-70 to 85 (-94 to 185)	8000	44.10	13.50	0.17
Operation	°C (°F)	-50 to 85 (-58 to 185)	10000	50.30	15.30	0.15
			12000	56.10	17.10	0.13
			15800	66.20	20.20	0.11

### RELATED PRODUCTS

#### Premium Connector Series E01/D01

Model Number	Type
<a href="#">43M-LCF14-E01</a>	4.3-10 Male
<a href="#">NM-LCF14-E01</a>	N Type Male
<a href="#">NF-LCF14-E01</a>	N Type Female
<a href="#">NMR-LCF14-E01</a>	N Type Male Right Angle

#### Tools for Series D01

<a href="#">TRIM-SET-L14-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IL14-D01</a>	Univ. Trimming Tool Insert

#### Accessories

Model Number	Type
<a href="#">RSB-S38/L14</a>	Stainless Steel Clamp
<a href="#">GKSPEED20-14C</a>	Grounding Kit, CCA Wire
<a href="#">GKSPEED20-14P</a>	Grounding Kit, Premium
<a href="#">TRIM-T01</a>	Hand Tool Kit

## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**LCF38 Series: 13.5 GHz**

### ORDERING INFORMATION

Jacketing Options	Standard Attenuation Cable Model Numbers
Outdoor standard:	<a href="#">LCF38-50J</a>
Indoor flame retardant:	<a href="#">LCF38-50JFN</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS			ELECTRICAL SPECIFICATIONS			
Dimensions Over Jacket	mm (in)	11.2 (0.441)	Operating Frequency Band	GHz	13.5	
Min. Bending Radius, Single	mm (in)	50 (2)	Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222)	
Min. Bending Radius, Repeated	mm (in)	95 (4)			Premium 23 (1.152)	
Jacket Type	Polyethylene, PE				Premium 24 (1.135)	
Bending Moment	Nm (lb-ft)	1.9 (1.4)	ATTENUATION			
Tensile Strength	N (lb)	530 (119)	Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW
Recommended/Maximum Clamp Spacing	m (ft)	0.5 / 1 (1.75 / 3.25)	800	10.10	3.07	0.72
<b>TEMPERATURE SPECIFICATIONS</b>			1800	15.50	4.74	0.47
Installation	°C (°F)	-40 to 60 (-40 to 140)	2400	18.20	5.54	0.40
Installation - JFNA	°C (°F)	-25 to 60 (-13 to 140)	3500	22.40	6.82	0.32
Storage	°C (°F)	-70 to 85 (-94 to 185)	5000	27.40	8.34	0.27
Operation	°C (°F)	-50 to 85 (-58 to 185)	6000	30.30	9.25	0.24
			8000	35.80	10.90	0.20
			10000	40.80	12.40	0.18
			12000	45.50	13.90	0.16
			13500	48.80	14.90	0.15

### RELATED PRODUCTS

#### Standard Connectors

Model Number	Type
<a href="#">NM-LCF38-070</a>	N Type Male
<a href="#">NF-LCF38-070</a>	N Type Female
<a href="#">NMR-LCF38-071</a>	N Type Male Right Angle

#### Tools for Series C03

<a href="#">TRIM-38-L03</a>	Combination Prep Tool
-----------------------------	-----------------------

#### Premium Connector Series E01

Model Number	Type
<a href="#">43M-LCF38-E01</a>	4.3-10 Male
<a href="#">NM-LCF38-E01</a>	N Type Male
<a href="#">NF-LCF38-E01</a>	N Type Female
<a href="#">NMR-LCF38-E01</a>	N Type Male Right Angle

#### Tools for Series E01

<a href="#">TRIM-SET-L38-E01</a>	Universal Trimming Tool
<a href="#">TRIM-IL38-E01</a>	Univ. Trimming Tool Insert

#### Accessories

Model Number	Type
<a href="#">RSB-38/12</a>	RSB Clamp Lining
<a href="#">RSB-12</a>	RSB Clip (in Combination)
<a href="#">TRIM-T01</a>	Hand Tool Kit



## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**LCF12 Series: 8.8 GHz**

### ORDERING INFORMATION

Jacketing Options	Premium Attenuation Cable Model Numbers	Lite Low-Loss Cable Model Numbers
Outdoor standard:	<a href="#">LCF12-50J</a>	<a href="#">LCF12-50JL</a>
Indoor flame retardant:	<a href="#">LCF12-50JFN</a>	<a href="#">LCF12-50JFNL</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS			ELECTRICAL SPECIFICATIONS						
Dimensions Over Jacket	mm (in)	15.9 (0.62)	Operating Frequency Band	GHz	8.8				
Min. Bending Radius, Single	mm (in)	70 (3)	Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222)				
Min. Bending Radius, Repeated	mm (in)	125 (5)			Premium 23 (1.152)				
Jacket Type	Polyethylene, PE				Premium 24 (1.135)				
Bending Moment	Nm (lb-ft)	6.5 (4.8)	ATTENUATION						
Tensile Strength	N (lb)	Copper 1050 (236) Aluminum 800 (180)	Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW			
Recommended/Maximum Clamp Spacing	m (ft)	0.6 / 1 (2 / 3.25)	Version	JA	JL	JA	JL	JA	JL
<b>TEMPERATURE SPECIFICATIONS</b>			800	6.48	6.94	1.98	2.12	1.16	1.28
Installation	°C (°F)	-40 to 60 (-40 to 140)	1800	10.10	10.70	3.07	3.26	0.75	0.83
Installation - JFNA	°C (°F)	-25 to 60 (-13 to 140)	2200	11.30	11.90	3.44	3.63	0.67	0.75
Storage	°C (°F)	-70 to 85 (-94 to 185)	2600	12.40	13.10	3.78	3.98	0.61	0.68
Operation	°C (°F)	-50 to 85 (-58 to 185)	3500	14.70	15.40	4.47	4.69	0.51	0.58
			5000	18.00	18.80	5.50	5.72	0.42	0.47
			6000	20.70	20.80	6.30	6.34	0.37	0.43
			8000	23.80	24.50	7.26	7.47	0.32	0.36
			8800	25.20	25.90	7.69	7.90	0.30	0.34

### RELATED PRODUCTS

#### Standard Connector Series C03

Model Number	Type
<a href="#">716M-LCF12-C03</a>	7/16 Male
<a href="#">716F-LCF12-C03</a>	7/16 Female
<a href="#">43M-LCF12-C03</a>	4.3-10 Male
<a href="#">43MH-LCF12-C03</a>	4.3-10 Male, Hand Screw
<a href="#">43MP-LCF12-C03</a>	4.3-10 Male, Push-Pull
<a href="#">43F-LCF12-C03</a>	4.3-10 Female
<a href="#">NM-LCF12-C03</a>	N Type Male
<a href="#">NF-LCF12-C03</a>	N Type Female
<a href="#">716MR-LCF12-C03</a>	7/16 Male Right Angle
<a href="#">43MR-LCF12-C03</a>	4.3-10 Male Right Angle
<a href="#">NMR-LCF12-C02</a>	N Type Male Right Angle

#### Tools for Series C03

<a href="#">TRIM-SET-L12-C02</a>	Universal Trimming Tool
<a href="#">TRIM-IL12-C02</a>	Trimming Tool Insert

#### Premium Connector Series E01

Model Number	Type
<a href="#">716M-LCF12-E01</a>	7/16 Male
<a href="#">716F-LCF12-E01</a>	7/16 Female
<a href="#">43M-LCF12-E01</a>	4.3-10 Male
<a href="#">43F-LCF12-E01</a>	4.3-10 Female
<a href="#">NM-LCF12-E01</a>	N Type Male
<a href="#">NF-LCF12-E01</a>	N Type Female
<a href="#">716MR-LCF12-E01</a>	7/16 Male Right Angle
<a href="#">43MR-LCF12-E01</a>	4.3-10 Male Right Angle
<a href="#">NMR-LCF12-E01</a>	N Type Male Right Angle

#### Tools for Series E01

<a href="#">TRIM-SET-L12-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IL12-D01</a>	Univ. Trimming Tool Insert
<a href="#">TRIM-LCF12-D01-A</a>	Automatic Trimming Tool
<a href="#">TRIM-B13</a>	Blades for Automatic Tool

#### Accessories

Model Number	Type
<a href="#">HOIST1-12L</a>	Hoisting Grip
<a href="#">GKSPEED20-12C</a>	Grounding Kit, CCA Wire
<a href="#">GKSPEED20-12P</a>	Grounding Kit, Premium
<a href="#">GKSPEED20-12S</a>	Grounding Kit, Standard
<a href="#">GKSPEED60-12S</a>	Grounding Kit, High Speed
<a href="#">JSTRIP-12-3</a>	Jacket Stripping Tool
<a href="#">CEAR-12</a>	Connector Grounding Kit
<a href="#">BOOT4-12-4</a>	Feed Through Assembly
<a href="#">BOOT-CP-12</a>	Cushion Plug
<a href="#">RSB-12</a>	Stainless Steel Clamp
<a href="#">TRIM-T01</a>	Hand Tool Kit

#### Multi-Block Hangers

<a href="#">MBH12-2-F</a>	2 per layer, 1 layer, 2 runs
<a href="#">MBH12-6-F</a>	2 per layer, 3 layers, 6 runs
<a href="#">MBHS12-1-F</a>	1 per layer, 1 layer, 1 run
<a href="#">MBHS12-2-F</a>	1 per layer, 2 layers, 2 runs
<a href="#">MBHS12-3-F</a>	1 per layer, 3 layers, 3 runs



## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**LCF78 Series: 5 GHz**



### ORDERING INFORMATION

Jacketing Options	Premium Attenuation Cable Model Numbers	Lite Low-Loss Cable Model Numbers
Outdoor standard:	<a href="#">LCF78-50JA</a>	<a href="#">LCF78-50JL</a>
Indoor flame retardant:	<a href="#">LCF78-50JFNA</a>	<a href="#">LCF78-50JFNL</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS			ELECTRICAL SPECIFICATIONS						
Dimensions Over Jacket	mm (in)	27.8 (1.094)	Operating Frequency Band	GHz	5				
Min. Bending Radius, Single	mm (in)	120 (5)	Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222)				
Min. Bending Radius, Repeated	mm (in)	250 (10)			Premium 23 (1.152)				
Jacket Type	Polyethylene, PE				Premium 24 (1.135)				
Bending Moment	Nm (lb-ft)	13 (10)	ATTENUATION						
Tensile Strength	N (lb)	1440 (324)	Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW			
Recommended/Maximum Clamp Spacing	m (ft)	0.8 / 1 (2.75 / 3.25)	<b>Version</b>	<b>JA</b>	<b>JL</b>	<b>JA</b>	<b>JL</b>		
TEMPERATURE SPECIFICATIONS			800	3.48	3.72	1.06	1.13	2.41	2.85
Installation	°C (°F)	-40 to 60 (-40 to 140)	1800	5.44	5.76	1.66	1.76	1.54	1.84
Installation - JFNA	°C (°F)	-25 to 60 (-13 to 140)	2200	6.09	6.43	1.86	1.96	1.38	1.65
Storage	°C (°F)	-70 to 85 (-94 to 185)	2600	6.70	7.05	2.04	2.15	1.25	1.50
Operation	°C (°F)	-50 to 85 (-58 to 185)	3600	8.30	8.47	2.53	2.58	1.03	1.25
			4000	8.60	8.98	2.62	2.74	0.97	1.18
			5000	9.81	10.20	2.99	3.11	0.85	1.04

### RELATED PRODUCTS

#### Standard Connector Series C03

Model Number	Type
<a href="#">716M-LCF78-C03</a>	7/16 Male
<a href="#">716F-LCF78-C03</a>	7/16 Female
<a href="#">43M-LCF78-C03</a>	4.3-10 Male
<a href="#">43MH-LCF78-C03</a>	4.3-10 Male, Hand Screw
<a href="#">43MP-LCF78-C03</a>	4.3-10 Male, Push-Pull
<a href="#">43F-LCF78-C03</a>	4.3-10 Female
<a href="#">NM-LCF78-C03</a>	N Type Male
<a href="#">NF-LCF78-C03</a>	N Type Female

#### Tools for Series C03

<a href="#">TRIM-SET-L78-C02</a>	Universal Trimming Tool
<a href="#">TRIM-IL78-C02</a>	Trimming Tool Insert
<a href="#">TRIM-FL78</a>	Flaring Tool

#### Premium Connector Series E01

Model Number	Type
<a href="#">716M-LCF78-E01</a>	7/16 Male
<a href="#">716F-LCF78-E01</a>	7/16 Female
<a href="#">43M-LCF78-E01</a>	4.3-10 Male
<a href="#">43F-LCF78-E01</a>	4.3-10 Female
<a href="#">NM-LCF78-E01</a>	N Type Male
<a href="#">NF-LCF78-E01</a>	N Type Female

#### Tools for Series E01

<a href="#">TRIM-SET-L78-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IL78-D01</a>	Univ. Trimming Tool Insert
<a href="#">TRIM-LCF78-D01-A</a>	Automatic Trimming Tool
<a href="#">TRIM-FL78</a>	Flaring Tool

#### Accessories

Model Number	Type
<a href="#">HOIST1-78L</a>	Hoisting Grip
<a href="#">GKSPEED20-78C</a>	Grounding Kit, CCA Wire
<a href="#">GKSPEED20-78P</a>	Grounding Kit, Premium
<a href="#">GKSPEED20-78S</a>	Grounding Kit, Standard
<a href="#">GKSPEED60-78S</a>	Grounding Kit, High Speed
<a href="#">JSTRIP-78-2</a>	Jacket Stripping Tool
<a href="#">CEAR-78</a>	Connector Grounding Kit
<a href="#">BOOT4-78-4</a>	Feed Through Assembly
<a href="#">BOOT-CP-78</a>	Cushion Plug
<a href="#">RSB-78</a>	Stainless Steel Clamp
<a href="#">TRIM-T01</a>	Hand Tool Kit

#### Multi-Block Hangers

<a href="#">MBH78-2-F</a>	2 per layer, 1 layer, 2 runs
<a href="#">MBH78-6-F</a>	2 per layer, 3 layers, 6 runs
<a href="#">MBHS78-1-F</a>	1 per layer, 1 layer, 1 run
<a href="#">MBHS78-2-F</a>	1 per layer, 2 layers, 2 runs
<a href="#">MBHS78-3-F</a>	1 per layer, 3 layers, 3 runs



## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**LCFS114 Series: 3.7 GHz**



### ORDERING INFORMATION

Jacketing Options	Premium Attenuation Cable Model Numbers
Outdoor standard:	<a href="#">LCFS114-50JA</a>
Indoor flame retardant:	<a href="#">LCFS114-50JFNA</a>
Indoor CPR certified	<a href="#">LCFS114-50CPR</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS			ELECTRICAL SPECIFICATIONS			
Dimensions Over Jacket	mm (in)	39 (1.54)	Operating Frequency Band	GHz	3.7	
Min. Bending Radius, Single	mm (in)	200 (8)	Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222)	
Min. Bending Radius, Repeated	mm (in)	380 (15)			Premium 23 (1.152)	
Jacket Type	Polyethylene, PE				Premium 24 (1.135)	
Bending Moment	Nm (lb-ft)	Copper 43 (32) Aluminum 22 (16.2)	ATTENUATION			
Tensile Strength	N (lb)	Copper 2490 (560) Aluminum 1850 (416)	Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW
Recommended/Maximum Clamp Spacing	m (ft)	1 / 1.2 (3.25 / 4)	800	2.47	0.75	4.45
TEMPERATURE SPECIFICATIONS			1900	4.00	1.22	2.75
Installation	°C (°F)	-40 to 60 (-40 to 140)	2200	4.35	1.33	2.53
Installation - JFNA	°C (°F)	-25 to 60 (-13 to 140)	2600	4.80	1.46	2.29
Storage	°C (°F)	-70 to 85 (-94 to 185)	2700	4.90	1.49	2.24
Operation	°C (°F)	-50 to 85 (-58 to 185)	3000	5.21	1.59	2.11
			3300	5.51	1.68	2.00
			3600	5.80	1.77	1.90
			3700	5.90	1.80	1.86

### RELATED PRODUCTS

#### Standard Connector Series C02

Model Number	Type
<a href="#">716M-LCF114-C02</a>	7/16 Male
<a href="#">716F-LCF114-C02</a>	7/16 Female
<a href="#">NM-LCF114-C02</a>	N Type Male
<a href="#">NF-LCF114-C02</a>	N Type Female

#### Tools for Series C02

<a href="#">TRIM-SET-L114-C02</a>	Universal Trimming Tool
<a href="#">TRIM-IL114-C02</a>	Trimming Tool Insert

#### Premium Connector Series E01

Model Number	Type
<a href="#">716M-LCF114-E01</a>	7/16 Male
<a href="#">716F-LCF114-E01</a>	7/16 Female
<a href="#">43M-LCF114-E01</a>	4.3-10 Male
<a href="#">43F-LCF114-E01</a>	4.3-10 Female
<a href="#">NM-LCF114-E01</a>	N Type Male
<a href="#">NF-LCF114-E01</a>	N Type Female

#### Tools for Series E01

<a href="#">TRIM-SET-L114-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IL114-D01</a>	Univ. Trimming Tool Insert

#### Accessories

Model Number	Type
<a href="#">HOIST1-114L</a>	Hoisting Grip
<a href="#">GKSPEED20-114C</a>	Grounding Kit, CCA Wire
<a href="#">GKSPEED20-114P</a>	Grounding Kit, Premium
<a href="#">GKSPEED60-114S</a>	Grounding Kit, High Speed
<a href="#">JSTRIP-114-2</a>	Jacket Stripping Tool
<a href="#">CEAR-114</a>	Connector Grounding Kit
<a href="#">RSB-114</a>	Stainless Steel Clamp
<a href="#">TRIM-T01</a>	Hand Tool Kit

#### Multi-Block Hangers

<a href="#">MBHS114-1-F</a>	1 per layer, 1 layer, 1 run
<a href="#">MBHS114-2-F</a>	1 per layer, 2 layers, 2 runs
<a href="#">MBHS114-3-F</a>	1 per layer, 3 layers, 3 runs



## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**LCF158 Series: 2.75 GHz**

### ORDERING INFORMATION

Jacketing Options	Premium Attenuation Cable Model Numbers
Outdoor standard:	<a href="#">LCF158-50JA</a>
Indoor flame retardant:	<a href="#">LCF158-50JFNA</a>
Indoor flame retardant:	<a href="#">LCF158-50CPR</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS			ELECTRICAL SPECIFICATIONS			
Dimensions Over Jacket	mm (in)	50.2 (1.98)	Operating Frequency Band	GHz	2.75	
Min. Bending Radius, Single	mm (in)	200 (8)	Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222)	
Min. Bending Radius, Repeated	mm (in)	500 (20)			Premium 23 (1.152)	
Jacket Type		Polyethylene, PE			Premium 24 (1.135)	
Bending Moment	Nm (lb-ft)	42 (31)	ATTENUATION			
Tensile Strength	N (lb)	2500 (562)	Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW
Recommended/Maximum Clamp Spacing	m (ft)	1.2 / 1.5 (4 / 5)	800	1.98	0.60	5.66
			1700	3.06	0.93	3.66
			2000	3.36	1.03	3.34
			2200	3.56	1.08	3.15
			2400	3.75	1.14	2.99
			2600	3.93	1.20	2.85
			2700	4.02	1.23	2.79
			2750	4.07	1.24	2.75

### RELATED PRODUCTS

#### Standard Connector Series C02

Model Number	Type
<a href="#">716M-LCF158-C02</a>	7/16 Male
<a href="#">716F-LCF158-C02</a>	7/16 Female
<a href="#">NM-LCF158-C02</a>	N Type Male
<a href="#">NF-LCF158-C02</a>	N Type Female

#### Tools for Series C02

<a href="#">TRIM-SET-L158-C02</a>	Universal Trimming Tool
<a href="#">TRIM-IL158-C02</a>	Trimming Tool Insert

#### Premium Connector Series E01

Model Number	Type
<a href="#">716M-LCF158-E01</a>	7/16 Male
<a href="#">716F-LCF158-E01</a>	7/16 Female
<a href="#">43M-LCF158-E01</a>	4.3-10 Male
<a href="#">43F-LCF158-E01</a>	4.3-10 Female
<a href="#">NM-LCF158-E01</a>	N Type Male
<a href="#">NF-LCF158-E01</a>	N Type Female

#### Tools for Series E01

<a href="#">TRIM-SET-L158-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IL158-D01</a>	Univ. Trimming Tool Insert

#### Accessories

Model Number	Type
<a href="#">HOIST1-158L</a>	Hoisting Grip
<a href="#">GKSPEED20-158C</a>	Grounding Kit, CCA Wire
<a href="#">GKSPEED20-158P</a>	Grounding Kit, Premium
<a href="#">GKSPEED60-158S</a>	Grounding Kit, High Speed
<a href="#">JSTRIP-158-2</a>	Jacket Stripping Tool
<a href="#">CEAR-158</a>	Connector Grounding Kit
<a href="#">BOOT4-158-1</a>	Feed Through Assembly
<a href="#">RSB-158</a>	Stainless Steel Clamp
<a href="#">TRIM-T01</a>	Hand Tool Kit

#### Multi-Block Hangers

<a href="#">MBH158-2-F</a>	2 per layer, 1 layer, 2 runs
<a href="#">MBH158-6-F</a>	2 per layer, 3 layers, 6 runs
<a href="#">MBHS158-1-F</a>	1 per layer, 1 layer, 1 run
<a href="#">MBHS158-2-F</a>	1 per layer, 2 layers, 2 runs



## CELLFLEX LOW-LOSS FOAM-DIELECTRIC COAXIAL CABLE

**LCF158 J Series: 2.75 GHz**

### ORDERING INFORMATION

Jacketing Options	Lite Low-Loss Cable Model Numbers
Outdoor standard:	<a href="#">LCF158-50JL</a>
Indoor flame retardant:	<a href="#">LCF158-50JFNL</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS			ELECTRICAL SPECIFICATIONS			
Dimensions Over Jacket	mm (in)	50.2 (1.98)	Operating Frequency Band	GHz	2.75	
Min. Bending Radius, Single	mm (in)	200 (8)	Max. VSWR / Return Loss	dB (VSWR)	Standard 20 (1.222)	
Min. Bending Radius, Repeated	mm (in)	500 (20)			Premium 23 (1.152)	
Jacket Type		Polyethylene, PE			Premium 24 (1.135)	
Bending Moment	Nm (lb-ft)	40.7 (30.7)	ATTENUATION			
Tensile Strength	N (lb)	1800 (405)	Frequency, MHz	dB per 100 m	dB per 100 ft	Power, kW
Recommended/Maximum Clamp Spacing	m (ft)	1.2 / 1.5 (4 / 5)	800	2.17	0.66	5.39
			1700	3.33	1.02	3.51
			2000	3.67	1.12	3.19
			2200	3.88	1.18	3.02
			2400	4.08	1.24	2.87
			2600	4.28	1.31	2.73
			2700	4.38	1.34	2.67
			2750	4.43	1.35	2.64

### RELATED PRODUCTS

#### Standard Connector Series C02

Model Number	Type
<a href="#">716M-LCF158-C02</a>	7/16 Male
<a href="#">716F-LCF158-C02</a>	7/16 Female
<a href="#">NM-LCF158-C02</a>	N Type Male
<a href="#">NF-LCF158-C02</a>	N Type Female

#### Tools for Series C02

<a href="#">TRIM-SET-L158-C02</a>	Universal Trimming Tool
<a href="#">TRIM-IL158-C02</a>	Trimming Tool Insert

#### Premium Connector Series E01

Model Number	Type
<a href="#">716M-LCF158-E01</a>	7/16 Male
<a href="#">716F-LCF158-E01</a>	7/16 Female
<a href="#">43M-LCF158-E01</a>	4.3-10 Male
<a href="#">43F-LCF158-E01</a>	4.3-10 Female
<a href="#">NM-LCF158-E01</a>	N Type Male
<a href="#">NF-LCF158-E01</a>	N Type Female

#### Tools for Series E01

<a href="#">TRIM-SET-L158-D01</a>	Universal Trimming Tool
<a href="#">TRIM-IL158-D01</a>	Univ. Trimming Tool Insert

#### Accessories

Model Number	Type
<a href="#">HOIST1-158L</a>	Hoisting Grip
<a href="#">GKSPEED20-158C</a>	Grounding Kit, CCA Wire
<a href="#">GKSPEED20-158P</a>	Grounding Kit, Premium
<a href="#">GKSPEED60-158S</a>	Grounding Kit, High Speed
<a href="#">JSTRIP-158-2</a>	Jacket Stripping Tool
<a href="#">CEAR-158</a>	Connector Grounding Kit
<a href="#">BOOT4-158-1</a>	Feed Through Assembly
<a href="#">RSB-158</a>	Stainless Steel Clamp
<a href="#">TRIM-T01</a>	Hand Tool Kit

#### Multi-Block Hangers

<a href="#">MBH158-2-F</a>	2 per layer, 1 layer, 2 runs
<a href="#">MBH158-6-F</a>	2 per layer, 3 layers, 6 runs
<a href="#">MBHS158-1-F</a>	1 per layer, 1 layer, 1 run
<a href="#">MBHS158-2-F</a>	1 per layer, 2 layers, 2 runs



## CLEARFILL®LINE PLENUM-RATED CABLES

RFS ClearFill®Line plenum-rated wideband cables deliver outstanding electrical and mechanical performance, and operate in frequencies from 380 MHz to 6 GHz to support all in-building wireless technologies and applications. These air dielectric coaxial cables are thoroughly tested for safe use within the “environmental air handling space” in ceilings as well as in more traditional plenum applications. They’re available in copper or lighter weight aluminum models to meet any installation requirements.

### IMPROVE IN-BUILDING WIRELESS NETWORK PERFORMANCE

ClearFill®Line plenum-rated cables provide low attenuation and excellent return loss.

FREQUENCY RANGE (MHz)	RETURN LOSS (dB)	VSWR
698-960	24	1.13
1395-1432	24	1.13
1700-2155	24	1.13
2300-2700	20	1.22
3550-4200	18	1.29
5150-6000	18	1.29

They also feature robust construction that reduces the risk of performance issues:

- A continuous, star-shaped dielectric provides complete support for the inner conductor to eliminate electrical and mechanical problems in tight bending areas.
- The solid outer conductor creates a continuous RFI/EMI shield that minimizes system interference.

### LEVERAGE NEW SPECTRUM

With wideband spectrum support up to 6 GHz, ClearFillLine plenum-rated cables make it easy to take advantage of newly available Citizens Broadband Radio Service (CBRS) spectrum in the 3.5 GHz band and LTE License Assisted Access (LAA) spectrum in the unlicensed 5 GHz band.

## Wideband operation

Support technologies and applications in bands ranging from 380MHz up to 6GHz

## CLEARFILL®LINE PLENUM-RATED CABLES

ICA12 Series: 6 GHz



### ORDERING INFORMATION

1/2" Plenum-Rated Cables Jacket Color	Wideband Copper Cables Model Numbers	Wideband Aluminum Cables Model Numbers
Blue	<a href="#">ICA12-50JPL</a>	<a href="#">ICA12-50JPLL</a>
Red	<a href="#">ICA12-50JPLR</a>	<a href="#">ICA12-50JPLLR</a>
Black	<a href="#">ICA12-50JPLB</a>	<a href="#">ICA12-50JPLLB</a>
White	<a href="#">ICA12-50JPLW</a>	<a href="#">ICA12-50JPLLW</a>

### PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS		
Dimensions Over Jacket	mm (in)	15.93 (0.627)
Min. Bending Radius, Single	mm (in)	76 (3)
Min. Bending Radius, Repeated	mm (in)	127 (5)
Jacket Type	PVC, Plenum Rated, UV rated to ASTM G155, Water-resistant	
Bending Moment	Nm (lb-ft)	Copper 4.1 (3) Aluminum 5.4 (4)
Tensile Strength	N (lb)	Copper 1112 (250) Aluminum 549 (150)
Recommended/Maximum Clamp Spacing	m (ft)	0.5 / 0.9 (1.8 / 3)

TEMPERATURE SPECIFICATIONS		
Installation	°C (°F)	-20 to 60 (-4 to 140)
Storage	°C (°F)	-40 to 85 (-40 to 185)
Operation	°C (°F)	-40 to 85 (-40 to 185)

ELECTRICAL SPECIFICATIONS		
Operating Frequency Band	GHz	6
Max. VSWR / Return Loss	dB (VSWR)	24 (1.13) @ 698-960 MHz
		24 (1.13) @ 1395-1432 MHz
		24 (1.13) @ 1700-2155 MHz
		20 (1.22) @ 2300-2700 MHz
		18 (1.29) @ 3550-4200 MHz
		18 (1.29) @ 5150-6000 MHz

ATTENUATION						
Frequency, MHz	dB per 100 m		dB per 100 ft		Power, kW	
Version	JPL	JPLL	JPL	JPLL	JPL	JPLL
800	6.64	7.28	2.02	2.22	1.09	1.06
1800	10.50	11.5	3.2	3.49	0.69	0.67
2200	11.80	12.80	3.59	3.92	0.62	0.61
2600	13.00	14.2	3.96	4.31	0.56	0.55
3600	15.80	17.10	4.81	5.22	0.47	0.46
4000	16.80	18.30	5.13	5.56	0.44	0.43
5000	19.30	20.90	5.88	6.36	0.38	0.38
6000	21.6	23.3	6.58	7.11	0.34	0.34

### RELATED PRODUCTS

#### Standard Connector Series C03/C02

Model Number	Type
<a href="#">716M-LCF12-C03</a>	7/16 Male
<a href="#">716F-LCF12-C03</a>	7/16 Female
<a href="#">43M-LCF12-C03</a>	4.3-10 Male
<a href="#">43F-LCF12-C03</a>	4.3-10 Female
<a href="#">NM-LCF12-C02-6</a>	N Type Male
<a href="#">NF-LCF12-C02-6</a>	N Type Female
<a href="#">NM-LCF12-C03</a>	N Type Male
<a href="#">NF-LCF12-C03</a>	N Type Female

#### Tools for Series C03/C02

<a href="#">TRIM-ICA12-C02</a>	Universal Trimming Tool
--------------------------------	-------------------------

#### Premium Connector Series E01

Model Number	Type
<a href="#">716M-LCF12-E01</a>	7/16 Male
<a href="#">716F-LCF12-E01</a>	7/16 Female
<a href="#">43M-LCF12-E01</a>	4.3-10 Male
<a href="#">43F-LCF12-E01</a>	4.3-10 Female
<a href="#">NM-LCF12-E01</a>	N Type Male
<a href="#">NF-LCF12-E01</a>	N Type Female

#### Tools for Series E01

<a href="#">TRIM-SET-L12-D01</a>	Universal Trimming Tool
----------------------------------	-------------------------

#### Accessories

Model Number	Type
<a href="#">HOIST1-12L</a>	Hoisting Grip
<a href="#">GKSPEED20-12C</a>	Grounding Kit, CCA Wire
<a href="#">GKSPEED20-12P</a>	Grounding Kit, Premium
<a href="#">GKSPEED20-12S</a>	Grounding Kit, Standard
<a href="#">GKSPEED60-12S</a>	Grounding Kit, High Speed
<a href="#">JSTRIP-12-3</a>	Jacket Stripping Tool
<a href="#">CEAR-12</a>	Connector Grounding Kit
<a href="#">BOOT4-12-4</a>	Feed Through Assembly
<a href="#">BOOT-CP-12</a>	Cushion Plug
<a href="#">RSB-12</a>	Stainless Steel Clamp
<a href="#">TRIM-T01</a>	Hand Tool Kit

#### Multi-Block Hangers

<a href="#">MBH12-2-F</a>	2 per layer, 1 layer, 2 runs
<a href="#">MBH12-6-F</a>	2 per layer, 3 layers, 6 runs
<a href="#">MBHS12-1-F</a>	1 per layer, 1 layer, 1 run
<a href="#">MBHS12-2-F</a>	1 per layer, 2 layers, 2 runs
<a href="#">MBHS12-3-F</a>	1 per layer, 3 layers, 3 runs

## GET HIGH-PERFORMANCE JUMPER CABLES FOR ANY APPLICATION, ANY SIZE

RFS is a global leader in RF jumper cables and offers a complete portfolio of jumper cables that meet any requirements.

**CELLFLEX Factory-Fit Jumpers** are ideal for indoor environments and other locations where jumper connectors do not require weatherproofing.

**CELLFLEX SecureFit Booted Jumpers** are ideal for outdoor environments and other locations where jumper connectors need to be protected from the elements.

*All of our CELLFLEX jumper cables support frequencies up to 6 GHz to simplify your network evolution and protect your investment.*

### CHOOSE FROM SUPER-FLEXIBLE AND LOW-LOSS JUMPER CABLES

CELLFLEX Factory-Fit Jumpers and CELLFLEX SecureFit Booted Jumpers are designed for seamless connection to our renowned CELLFLEX foam dielectric coaxial cables:



**CELLFLEX super-flexible jumper cables** combine outstanding bending characteristics and electrical performance to improve quality and efficiency in the most challenging deployment scenarios.

**CELLFLEX low-loss jumper cables** deliver extremely low attenuation that increases the efficiency of signal transfers in any RF system.

### MIX AND MATCH JUMPER CABLE CONFIGURATIONS AND FEATURES TO MEET APPLICATION AND SITE REQUIREMENTS

We offer a variety of features and configuration options for each jumper cable type and size. Options include:

- Jacket type: Standard or flame-retardant
- Connector type for each endpoint: NEX10, 4.3-10, N-Type or 7-16 DIN right-angled or straight connectors
- Performance: UltraPIM or Premium PIM
- Length: 1 m to 20 m or 3 ft to 50 ft

We manufacture and stock the most popular combinations and can deliver custom lengths when required.

### SIMPLIFY 4G, 5G AND SMALL CELL DEPLOYMENTS IN CROWDED URBAN ENVIRONMENTS

As you upgrade and add network technologies to already-crowded sites, the ability to make more coaxial cable connections in smaller spaces is crucial.

CELLFLEX super-flexible 1/4-inch jumpers with miniaturized NEX10 and 4.3-10 connectors make urban installations faster and easier. They're ideal for installations in highly constrained spaces, such as street poles, and for short-distance connections. To ensure optimal attenuation over longer distances, rely on our low-loss 1/2-inch jumper cables.



## GET HIGH-PERFORMANCE JUMPER CABLES FOR ANY APPLICATION, ANY SIZE

### MAINTAIN ULTRA-HIGH PERFORMANCE END-TO-END

You can't afford to compromise on performance. Jumper cables that provide the ultimate in electrical performance are essential to guarantee end-to-end transmission line performance and support the next generations of applications.

CELLFLEX jumper cables feature our industry-leading UltraPIM performance, and we guarantee the performance specifications for every jumper cable.

All of our jumpers are fully tested for PIM, VSWR (return loss) and interface performance. Test results are available online for products sold globally.

### GET MORE VALUE FROM EXISTING EQUIPMENT

We understand your need to extract maximum value from the investments you've already made in network equipment.

While some jumper cable vendors are discontinuing older connector types, such as N-Type and 7-16 DIN, we continue to offer the interfaces.

### BRING US YOUR TOUGHEST DEPLOYMENT CHALLENGES

We have the expertise and experience needed to adapt our jumper designs and deliver innovative, custom jumper cables that are designed to meet your unique requirements and resolve the most difficult installation challenges.

One of our recent innovations includes jumper cables with shortened, molded boots that fit within the available space on a specific outdoor small cell radio while still allowing a plastic cover to close over the end of the jumper.

### SUPPORT DEPLOYMENTS ANYWHERE IN THE WORLD

We understand your need to extract maximum value from the investments you've already made in network equipment. While some jumper cable vendors are discontinuing older connector types, such as N-Type and 7-16 DIN, we continue to offer the interfaces.



## CLUSTER CONNECTORS



### Make More Jumper Connections in Less Space

Our innovative new jumper cables with RF cluster connectors are ideal for connecting to highly integrated antennas that have a large number of RF ports in a very compact footprint.

Each cluster connector supports connections to multiple RF ports to enable

connections to more than 20 multiband 4T4R and 8T8R ports within the space of a typical antenna end cap.

Simplify your next deployment using cluster jumpers with MQ4/MQ5 connectors or M-LOC systems.

[LEARN MORE](#)



## PROTECT CRITICAL CONNECTIONS WITH THE ULTIMATE WEATHERPROOFING BOOT

RFS CELLFLEX SecureFit Booted Jumpers feature specially designed, injection-molded weatherproof boots that protect jumper connections from all forms of moisture — from rain to snow and ice — as well as salt, sand, dust and other contaminants that can corrode connectors, degrade connection quality and reduce connector lifespan.



**CELLFLEX SecureFit Booted Jumpers** are available in a wide variety of RFS jumper cable sizes, for all RFS-supported connector types and all RFS jumper configurations. In 2022, RFS has added smaller cable sizes and more models with right-angle and NEX10 connectors to the product portfolio.

With the addition of the new jumper models, RFS' SecureFit Booted Jumper portfolio now includes the following jumper sizes and factory-installed connectors:

- 1/4-inch and 3/8-inch jumpers with 4.3-10 or NEX10 connectors
- 1/2-inch jumpers with right-angle connectors
- 1/2-inch jumpers with NEX10 connectors

The boot's sleek, close-fitting design results in a small footprint that's ideal to protect any connection, including connections to multi-port equipment with tight connector spacing.

### UPGRADE TO FASTER, EASIER WEATHERPROOFING WITH CELLFLEX SECUREFIT BOOTED JUMPERS

With CELLFLEX SecureFit Booted Jumpers, you can quickly and easily add an additional level of sealing and strain relief to any connection with no need for installers to waste time and effort applying and removing sealing tape.

Installers can connect and disconnect our SecureFit Booted Jumpers far faster and easier than they can when sealing tape is used to protect connections. And no waste is generated, so installers never have to worry about garbage removal or clutter while they're working high on towers. There's also no risk that jumper cables can be damaged or installers injured as is the case when a knife is used to remove sealing tape from connections.


### ENSURE CONSISTENT AND RELIABLE WEATHERPROOFING ON ALL CONNECTIONS

The SecureFit boot design is the same no matter which connector type you're using or which equipment you're connecting to.

The ergonomic boot design allows installers to use a single hand to easily slide the boot into place over the connection and to remove the boot when needed. Installers quickly master the technique and can apply consistent and reliable weatherproofing across all connections with minimal training.

The lead time for CELLFLEX SecureFit Booted Jumpers is the same as our CELLFLEX Factory-Fit Jumpers, so there are no delays when booted jumpers are required.

*Protect your network investment and maintain premium performance with a reliable and exceptionally easy weatherproofing solution from RFS*



## UNLIMITED CONNECTIONS WITH THE RFS ADAPTER SERIES

### CONNECTIONS IN THE FIELD JUST GOT EASIER

RFS' new coaxial adapter series provides a fast, easy and cost-effective solution for jumper connections. With a large selection of both straight and right angle adapters, there is a model for every network requirement. Passive intermodulation specifications for all RFS adapters is < -163 dBc.



MODEL NUMBER (STRAIGHT)	MODEL NUMBER (RIGHT ANGLE)
<a href="#">716M-716F</a>	<a href="#">716M-R-716F</a>
<a href="#">716F-43F</a>	<a href="#">716M-R-716M</a>
<a href="#">716M-716M</a>	<a href="#">43M-R-43F</a>
<a href="#">716M-43M</a>	<a href="#">NM-R-NM</a>
<a href="#">716M-43F</a>	<a href="#">NM-R-NF</a>
<a href="#">716M-NM</a>	<a href="#">716F-R-716F</a>
<a href="#">716M-NF</a>	<a href="#">716F-R-43M</a>
<a href="#">43F-43F</a>	<a href="#">716F-R-43F</a>
<a href="#">43F-NM</a>	<a href="#">716F-R-NM</a>
<a href="#">43F-NF</a>	<a href="#">716F-R-NF</a>
<a href="#">43M-43M</a>	<a href="#">716M-R-43M</a>
<a href="#">43M-NM</a>	<a href="#">716M-R-43F</a>
<a href="#">43M-NF</a>	<a href="#">716M-R-NM</a>
<a href="#">NM-NM</a>	<a href="#">716M-R-NF</a>
<a href="#">NM-NF</a>	<a href="#">43F-R-43F</a>
<a href="#">NF-NF</a>	<a href="#">43F-R-NM</a>
<a href="#">716F-716F</a>	<a href="#">43F-R-NF</a>
<a href="#">716F-43M</a>	<a href="#">43M-R-43M</a>
<a href="#">716F-NM</a>	<a href="#">43M-R-NM</a>
<a href="#">716F-NF</a>	<a href="#">43M-R-NF</a>
<a href="#">43M-43F</a>	<a href="#">NF-R-NF</a>

### RFS offers a wide range of videos to make installation fast and easy:


- Install premium and standard connectors on CELLFLEX® cables of all sizes
- Install connectors onto RADIAFLEX® cables
- DragonSkin™ premium and standard connector installation
- Watch these and more on the RFS YouTube channel





## UNDERSTANDING **CABLE MODEL NAMES**

All RFS coaxial cable model names are based on a naming structure that tells you:




LCF CABLE TYPE	12 CABLE SIZE	50 CABLE IMPEDENCE	J JACKET TYPE	A CABLE SUFFIX	-BAA DESIGN VARIANT
<b>LCF</b> Low attenuation foam dielectric, corrugated	<b>14</b> 1/4-inch	<b>50</b> 50 Ohm	<b>J</b> Standard PE Jacket	<b>A</b> Low Loss Premium Attenuation	<b>-C</b> China
<b>LCFS</b> Corrugated IC	<b>38</b> 3/8-inch	<b>75</b> 75 Ohm	<b>JFN</b> Flame Retardant LSZH Jacket	<b>B</b> B Type – Lower technical performance	<b>-D</b> Germany
<b>SCF</b> Superflexible	<b>12</b> 1/2-inch		<b>CPR</b> Specific CPR Jacket	<b>L</b> Light cable – Aluminum OC	<b>-U</b> USA
<b>SCFS</b> Superflexible, standardized version	<b>78</b> 7/8-inch			<b>GR</b> Grey Jacket RAL7004	<b>-BAA</b> Compliant to the Buy America Act
<b>UCF</b> Ultraflexible, corrugated IC	<b>114</b> 1-1/4-inch			<b>RP</b> Rodent Protection – Nylon Jacket	<b>-B2</b> CPR rating B2
	<b>158</b> 1-5/8-inch			<b>TC</b> Phase stabilized after temperature cycles	<b>-B2d2</b> CPR rating B2d2
				<b>W</b> White Jacket	<b>-B2d0</b> CPR rating B2d0
					<b>-Cd2</b> CPR rating Cd2
					<b>-Cd0</b> CPR rating Cd0
					<b>-Dx</b> CPR rating D?



## UNDERSTANDING **JUMPER MODEL NAMES**

All RFS jumper model names are based on a naming structure that tells you:



7M & 43M CONNECTORS A & B	S12 CABLE TYPE	F JACKET TYPE	0100 CABLE LENGTH*	FFP JUMPER PERFORMANCE
<b>7M</b> 7-16 Male	<b>L38</b> 3/8" Low Loss Coax	<b>F</b> JFN Flame Retardant	<b>0100</b> 1 meter	<b>FFP</b> Factory-Fit Premium
<b>7F</b> 7-16 Female	<b>L12</b> 1/2" Low Loss Coax	<b>Blank</b> PE	<b>0200</b> 2 meter	<b>UPM</b> Ultra PIM Performance**
<b>7MR</b> 7-16 Male Right Angle	<b>S14</b> 1/4" Superflexible Coax		<b>0250</b> 2.5 meter	
<b>43M</b> 4.3-10 Male	<b>S38</b> 3/8" Superflexible Coax		<b>1000</b> 10 meter	
<b>43F</b> 4.3-10 Female	<b>S12</b> 1/2" Superflexible Coax		<b>1500</b> 15 meter	
<b>43MR</b> 4.3-10 Male Right Angle			<b>030</b> 3 feet	
<b>NM</b> N-Type Male			<b>060</b> 6 feet	
<b>NF</b> N-Type Female			<b>100</b> 10 feet	
<b>NMR</b> N-Type Male Right Angle			<b>150</b> 15 feet	
<b>NXM</b> NEX10 Male			<b>200</b> 20 feet	
<b>7MB</b> 7-16 Male with Weatherboots				
<b>7MRB</b> 7-16 Male Right Angle with Weatherboots				
<b>43MB</b> 4.3-10 Male with Weatherboots				
<b>43MRB</b> 4.3-10 Male Right Angle with Weatherboots				
<b>NMB</b> N-Type Male with Weatherboots				
<b>NMRB</b> N-Type Male Right Angle with Weatherboots				
<b>NXMB</b> NEX10 Male with Weatherboots				

NOTES:  
 \* 4 digits indicate meter length, 3 digits indicate feet length  
 Others lengths available on request  
 \*\* Available on request



# RADIO FREQUENCY SYSTEMS



**TO SERVE YOU BETTER**  
Any questions comments or  
suggestions that would help  
us improve our products and  
services? **Scan this QR code!**