Hanger, non-insulated, bolt-on for coaxial cable

HCA300, made of stainless steel

FEATURES / BENEFITS

Stainless steel hangers for supporting coaxial cable to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



		Clamp for 1-5/8" shown as a sample
External Document Links		Notes
		If using the Bolt-on hanger series in vertical runs, the hoisting grips
		need to be kept on the tower.
Technical features		
GENERAL SPECIFICATIONS		
Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Bolt-On, non-insulated
Transmission Line Type		HCA300
Cable Type		Air Dielectric
MECHANICAL SPECIFICATIONS		
Cable Size		3"
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1.2 (2.75 / 4)
TEMPERATURE SPECIFICATIONS		
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)
PACKAGING INFORMATION		
Package Quantity		10

www.rfsworld.com CLAMP-300-S REV: C REV DATE: 13 Jul 2023