



Hangers for the installation of HELIFLEX® cables on different supporting profiles.

Cable Clamp and Extended Counterbed hot-galvanized steel

Screw: stainless steel.

FEATURES / BENEFITS



picture shows the 1L4 version
for illustration purpose only

External Document Links

Notes

Hangers for angle iron 40mm (1.575")

Technical features

GENERAL SPECIFICATIONS

| | | |
|------------------------|--|---------------------------|
| Product Line | | Coaxial Cable Accessories |
| Product Type | | Hanger |
| Hanger Type | | Angle iron 40mm (1.575") |
| Transmission Line Type | | HCA300 |
| Cable Type | | Air Dielectric |

MECHANICAL SPECIFICATIONS

| | | |
|--|--------|--|
| Cable Size | | 3 |
| Material | | Cable Clamp : hot-dip galvanized Extended Counterbed : hot-dip galvanized Screw: Stainless steel |
| Recommended / Maximum Clamp Spacing | m (ft) | 0.8 / 1.2 (2.75 / 4) |

TEMPERATURE SPECIFICATIONS

| | | |
|-----------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |

PACKAGING INFORMATION

| | | |
|------------------|---------|-------------|
| Package Quantity | | 1 |
| Weight per piece | kg (lb) | 0.51 (1.12) |