



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment.

FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



NF-LCF78-C03

Technical features**GENERAL SPECIFICATIONS**

Transmission Line Type		Coaxial Cable	
Cable Size		7/8	
Cable Type		Foam Dielectric	
Model Series		LCF78-50 Series	RCF78-50 Series
Connector Interface		N	
Connector Type		OMNI FIT™ Standard	
Sealing Method		O-ring	
Gender		Female	

ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50	
3rd Order IM Product @ 2x20 Watts	dBc	-157 ; typical -160	
Maximum Frequency	GHz	6	
VSWR, Return Loss	VSWR (dB)	0 < f ≤ 1.0 GHz: 1.03 (36.6) 1.0 < f ≤ 2.7 GHz: 1.04 (34.1) 2.7 < f ≤ 3.7 GHz: 1.08 (28.3) 3.7 < f ≤ 5.0 GHz: 1.15 (23.1) 5.0 < f ≤ 6.0 GHz: 1.25 (19.1)	

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Trimetal/Silver	
Length	mm (in)	56.9 (2.24)	
Outer Diameter	mm (in)	35.5 (1.4)	
Inner Contact Attachment		Spring Finger	
Outer Contact Attachment		Spring C-Ring	

ACCESSORIES

Wrench size front	mm (in)	22 (0.87)	
Wrench size rear	mm (in)	32 (1.26)	
Trimming Tool		TRIM-SET-L78-C02	




NF-LCF78-C03

N Female Connector for 7/8" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

TESTING AND ENVIRONMENTAL

Waterproof Level		IP68
------------------	--	------



NF-LCF78-C03 Outline drawing

External Document Links

[Installation Instruction](#)

Notes