

 ${\sf RSB\,\text{-}Clip\,Stainless\,Steel\,Hanger\,.\,Quantity\,of\,cable\,gripping\,tabs\,for\,the\,various\,cable\,type\,may\,be\,different.}$

FEATURES / BENEFITS

The RSB-Clip is designed for the installation of feeder cables from sizes 1/4"up to 1-5/8". The clip is a universal clamp device and can be used in many mounting configuration. The RSB-Clip is made of stainless steel. The hanger is resistant against all environmental influences. Due to the mechanical construction, a cable deformation is impossible. Therefore, a deterioration of the electrical properties is avoided.



External Document Links Notes

Technical features

GENERAL SPECIFICATIONS

| Product Line | | Coaxial Cable Accessories |
|-------------------------------------|---------|-------------------------------|
| | | Radiating Cable Accessories |
| | | Hybrid Cable Accessories |
| Product Type | | Hanger |
| Hanger Type | | RSB-Clip |
| Transmission Line Type | | LCF12 |
| | | ALFU12 |
| | | RLKW12 |
| | | RLKU12 |
| | | RCF12 |
| | | HCA12-50 |
| | | RHCA12-50 |
| | | HB012 |
| Cable Type | | Coaxial Foam Dielectric |
| | | Radiating Cable |
| | | Hybrid |
| MECHANICAL SPECIFICATIONS | | |
| Cable Size | | 1/2 |
| Number of Cable / Waveguide Runs | | 1 |
| Material | | Stainless Steel |
| Drill Hole Size | mm (in) | 8 (0.315) |
| ACCESSORIES | | |
| Spare Part / Useful Accessories | | Cleat : RSB-310 |
| | | Anchor bar fixation : RSB-315 |
| TEMPERATURE SPECIFICATIONS | | |
| Installation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| PACKAGING INFORMATION | | |
| Package Quantity | | 10 |

RSB-12 REV : F REV DATE : 24 Feb 2023 www.rfsworld.com