

PRODUCT DATASHEET 716F-NM Coaxial Adapter 7-16 female - N male

Coaxial Adapter, 7-16 Female/N Male FEATURES / BENEFITS

Technical features

| Product Line | | Coaxial Cable Components |
|--------------------------------------|-----------|----------------------------------------------------------------------------------------|
| Product Type | | Coaxial Adapter |
| MECHANICAL SPECIFICATIONS | | |
| Connector A | | 7-16 DIN Female |
| Center Contact Connector A | | Phosphor Bronze, silver plated |
| Outer Contact Connector A | | Brass, Tri metal alloy plated |
| Connector B | | N Male |
| Center Contact Connector B | | Phosphor Bronze, silver plated |
| Outer Contact Connector B | | Brass, Tri metal alloy plated |
| Dielectric | | PTFE |
| Gasket | | Silicone rubber |
| Sealing class | | IP68, connected |
| ELECTRICAL SPECIFICATIONS | | |
| Frequency Range - MHz | | DC - 6000 |
| VSWR, Return Loss | VSWR (dB) | 0-2000 MHz: 1.04 (34.15) 2000-3000 MHz: 1.06 (30.71) 3000-6000 MHz: 1.10 (26.44) |
| Insertion Loss, dB (Max) | dB | 0.05 |
| 3rd Order IM Product @ 2x20 Watts | dBc | -163 |
| TEMPERATURE SPECIFICATIONS | | |
| Operation Temperature | °C (°F) | -45 to 85 (-49 to 185) |
| PACKAGING INFORMATION | | |
| Package Quantity | | 1 |
| External Document Links | | Notes |

716F-NM

REV DATE : 19 Apr 2023

www.rfsworld.com