PRODUCT DATASHEET

TF100-BW1-120M

TwistFlex PBR/UBR100, 1.2m

Twistable and flexible rectangular waveguide R100,
with PBR/UBR 100 flanges. Length = 1.2m,
core with environmental impact resistant
molded rubber jacket. Hardware and gasket (for PDR/PBR flanges) included.

FEATURES / BENEFITS

Waveguide installation

- The flexible and twistable rectangular waveguide component eliminates installation difficulties
- It isolates vibration
- It provides simple aid to positioning of antennas

Technical features

STRUCTURE		
Type of Rectangular Waveguide Component		TwistFlex
Waveguide Size IEC (EIA)		R100 (WR90)
Flange A		PBR100
Flange B		UBR100
Flange Finish		Brass un-plated
Package Quantity		1
ELECTRICAL SPECIFICATIONS		
Frequency Range	GHz	8.2 - 12.4
Minimum Return Loss (max. VSWR)	dB (VSWR)	26.4 (1.10)
Attenuation	dB	0.48
Power rating	W	1000
MECHANICAL SPECIFICATIONS		
Maximum Twist	degree/m (degree/ft)	156 (47.6)
Minimum Bending Radius E-Plane	mm (in)	66 (2.6)
Minimum Bending Radius H-Plane	mm (in)	130 (5.1)
Length	mm (in)	1200 (47.2)
MATERIAL		
Material		Core: Brass silver plated Jacket: Vulcanised Neoprene Rubber Flange: Brass
Color		Black

External Document Links

AN 030707-8 Application note for RFS Twistflex

Notes

All values nominal unless tolerances provided; information contained in the present datasheet is subject to confirmation at time of ordering