Package Quantity

Coaxial Adapter, 4.3-10 Male / 4.3-10 Male 42. 3REF. **FEATURES / BENEFITS** S22.0 SW18.0 S22. 0 324. 324. External Document Links Notes **Technical features STRUCTURE Product Line** Coaxial Cable Components **Product Type** Coaxial Adapter **MECHANICAL SPECIFICATIONS** Connector A 4.3-10 Male **Center Contact Connector A** Copper Alloy, silver plated **Outer Contact Connector A** Copper Alloy, CuSnZn plated **Connector B** 4.3-10 Male **Center Contact Connector B** Copper Alloy, silver plated **Outer Contact Connector B** Copper Alloy, CuSnZn plated Dielectric PTFE **Sealing class** IP68, connected **ELECTRICAL SPECIFICATIONS** Frequency Range - MHz DC - 6000 DC TO 2GHz VSWR 1.04 (34.15) **VSWR**, Return Loss VSWR (dB) 2 TO 3GHz VSWR 1.06 (30.71) 3 TO 6GHz VSWR 1.10 (26.44) Insertion Loss, dB (Max) dB 0.05 3rd Order IM Product @ 2x20 dBc -163 Watts **PACKAGING INFORMATION**

43M-43M REV : C REV DATE : 19 Apr 2023 www.rfsworld.com

1