



CELLFLEX® 3/8" superflexible cable

FEATURES / BENEFITS

• **Ultra Low Attenuation**

The reduced attenuation of CELLFLEX® coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.

• **Complete Shielding**

The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.

• **Low VSWR**

Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.

• **Outstanding Intermodulation Performance**

CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.

• **High Power Rating**

Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.

• **Wide Range of Application**

Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects



Technical features

INFORMATION

Applications	OEM jumpers, BTS inter-cabinet connections, GPS lines, intended for outdoor usage
---------------------	---

STRUCTURE

Size		3/8
Inner Conductor	mm (in)	2.6 (0.102)
Inner Conductor Material		Copper-Clad Aluminum Wire
Dielectric	mm (in)	6.3 (0.248)
Dielectric Material		Foam Polyethylene
Outer Conductor	mm (in)	9.1 (0.358)
Outer Conductor Material		Corrugated Copper
Jacket	mm (in)	10.2 (0.402)
Jacket Material		Black Polyethylene

TESTING AND ENVIRONMENTAL

Phase Stabilized		Phase stabilized and phase matched cables and accessories are available upon request.
Compliance		DIN EN ISO 9001:2015 ISO 14001:2015 RoHS 2011/65/EU - China RoHS SJ/T 11364-2006 REACH (EC 1907/2006) UL1581 - UV Resistance Jacket IEC 60754-1/-2
Installation Temperature	°C(°F)	-40 to 60 (-40 to 140)
Storage Temperature	°C (°F)	-70 to 85 (-94 to 185)
Operation Temperature	°C(°F)	-50 to 85 (-58 to 185)



ELECTRICAL SPECIFICATIONS

Impedance	Ω	50 +/- 1
Maximum Frequency	GHz	13.4
Velocity	%	81
Capacitance	pF/m (pF/ft)	82 (25)
Inductance	uH/m (uH/ft)	0.207 (0.063)
Peak Power Rating	kW	11.9
RF Peak Voltage	Volts	1090
Jacket Spark	Volt RMS	5000
Inner Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	5.52 (1.68)
Outer Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	7.3 (2.23)
Passive Intermodulation PIM	min. dBC	-160
Return Loss (VSWR) Performance	Standard 20dB (1.222) / Premium 23/24dB (1.152/1.135) on specified frequencies	

MECHANICAL SPECIFICATIONS

Cable Weight, Nominal	kg/m (lb/ft)	0.1 (0.06)
Minimum Bending Radius, Repeated Bends	mm (in)	25 (0.984)
Tensile Strength	N (lb)	600 (135)
Recommended / Maximum Clamp Spacing	m (ft)	0.25 / 0.25 (0.8 / 0.8)

ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
1	0.41	0.12	19.43
100	4.21	1.28	1.88
200	6.04	1.84	1.31
450	9.31	2.84	0.85
700	11.83	3.61	0.67
800	12.73	3.88	0.62
900	13.58	4.14	0.58
1800	20.05	6.11	0.39
2000	21.30	6.49	0.37
2200	22.51	6.86	0.35
2400	23.67	7.21	0.33
2700	25.35	7.73	0.31
3000	26.97	8.22	0.29
3500	29.55	9.01	0.27
4000	32.00	9.75	0.25
5000	36.62	11.16	0.22
13400	68.30	20.82	0.12



RELATED PRODUCTS

Connector Interface	Premium Connector Series E01	Premium Connector Series D01 *only on request
N Male	NM-SCF38-E01	NM-SCF38-D01
N Female	NF-SCF38-E01	NF-SCF38-D01
4.3-10 Male	43M-SCF38-E01	
Mandatory Tool	TRIM-SET-S38-D01	
Tool Information	Universal Trimming Tool For *-D01 And *-E01 Connector Series	
Installation Video		
General Accessories		
Hand Tool Kit		TRIM-T01
Grounding Kit		EAR-38-S

[External Document Links](#)

[CELLFLEX Drum Selection Guide](#)

[Notes](#)