



Standard connector for FLEXWELL® elliptical waveguide E220 with PBR220 flange, Plast 2000 sealed frequency range: 21.2 - 23.6 GHz

**FEATURES / BENEFITS**

**Superior Design**

- Due to the precise manufacturing no tuning screws are necessary
- The terminations are brass passivated for good electrical performance
- A gas inlet is included

**Quick & Easy Installation**

- Different flaring tools are available
- No tuning in the field



**Technical features**

**STRUCTURE**

Transmission Line Type		Elliptical Waveguide
Cable Type		E220
Model Series		E220 Series
Connector Frequency Range	GHz	21.2 - 23.6
Connector Type		Fixed
Sealing Method		Plast 2000
Plating Outer/Inner		Brass
Waterproof Level		IP68
Gas Inlet		G 1/8
Connector Interface		PBR220

**MECHANICAL SPECIFICATIONS**

Length	mm (in)	93 (3.7)
Outer Diameter	mm (in)	40 (1.6)
Weight	kg (lb)	0.4 (0.88)
Sealing Volume	cm <sup>3</sup> (ounces)	20 ( 0.68)

**External Document Links**

[Installation Instruction](#)

**Notes**

Sealing component PLAST 2000 is **not** part of the connector delivery and must be ordered separately.