4" Feed Through Boot Assembly Hole for E60 Waveguide FEATURES / BENEFITS

These innovative boot assemblies feature a one-piece design which reduces installation time. The split, one-piece style simplifies clamping and frees the installers hands to position the cable runs. Boot assemblies are designed to be fitted onto 4" entry panels in wall/roof feed-through applications. The durable boot is designed to meet ASTM-D2000 and SAE J200 specifications. Each boot assembly includes the boot, two round member adapter clamps which fit inside the boot assembly to hold the waveguide in place.



Picuture shows BOOT4-065 for illustration

		purpose
External Document Links		Notes
Technical features		
STRUCTURE		
Product Line		Elliptical Waveguide Accessories
Product Type		Wall/Roof Feed-Through System
Feed-Through Component		Boot Assembly
Transmission Line Type		E60
MECHANICAL SPECIFICATIONS		
Feed-Through Hole Diameter	mm (in)	102 (4)
Insert Holes		1
Color		Black
Material		EPDM rubber
TEMPERATURE SPECIFICATIONS		
Operation Temperature, °C°F)	°C(°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C(°F)	-50 to 85 (-58 to 185)
PACKAGING INFORMATION		
Package Quantity		1
Weight per piece	kg (lb)	0.7 (1.6)
Box Dimensions (Bulk Shipping), L x W x H	mm (in)	635 x 330 x 178 (25 x 13 x 7)

BOOT4-060 REV : A REV DATE : 12 Apr 2024 www.rfsworld.com