



CLAMP-114

Cable hanger, non-insulated, bolt-on, for 1 1/4" coaxial cable and elliptical waveguide E65 and E70

Hanger, non-insulated, bolt-on for coaxial cable
LCF114 / LCFS114 / RCF114
and for elliptical waveguide E65/EP65 and E70/EP70
made of stainless steel, kit of 10

FEATURES / BENEFITS

Stainless steel hangers for supporting elliptical waveguide or coaxial cable to tower.
Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs,
member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters
through slot



Technical features

GENERAL SPECIFICATIONS

| | | |
|-------------------------------|--|--|
| Product Line | | Coaxial Cable Accessories Radiating Cable Accessories Elliptical Waveguide Accessories Hybrid Cable Accessories |
| Product Type | | Hanger |
| Hanger Type | | Bolt-On, non-insulated |
| Transmission Line Type | | LCF114 LCFS114 RCF114 UCF114 E65 EP65 E70 EP70 HB114 |
| Cable Type | | Coaxial Foam Dielectric Radiating Cable Hybrid |

MECHANICAL SPECIFICATIONS

| | | |
|---|--|-----------------|
| Cable Size | | 1-1/4 |
| Number of Cable / Waveguide Runs | | 1 |
| Material | | Stainless Steel |

TEMPERATURE SPECIFICATIONS

| | | |
|------------------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |

PACKAGING INFORMATION

| | | |
|-------------------------|--|----|
| Package Quantity | | 10 |
|-------------------------|--|----|

[External Document Links](#)

[Notes](#)