



**CLAMP-12**

Cable hanger, non-insulated, bolt-on, for 1/2" coaxial cable and elliptical waveguide

Hanger, non-insulated, bolt-on for coaxial cable  
LCF12 / RCF12 / ICA12-50JPL / DragonSkin 2HB12 / E/EP185, made of stainless steel, kit of 10

**FEATURES / BENEFITS**

Stainless steel hangers for supporting elliptical waveguide or coaxial cable to tower/inbuilding. Recommended spacing 1m (3 feet) for general application and 0.6m (2 feet) for RFS DragonSkin 2HB12 cable. Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



**Technical features**

**GENERAL SPECIFICATIONS**

<b>Product Line</b>		Coaxial Cable Accessories Radiating Cable Accessories Elliptical Waveguide Accessories Hybrid Cable Accessories
<b>Product Type</b>		Hanger
<b>Hanger Type</b>		Bolt-On, non-insulated
<b>Transmission Line Type</b>		LCF12 RCF12 ICA12-50 DragonSkin 2HB12-50 HB114 E/EP185
<b>Cable Type</b>		Air Dielectric Coaxial Foam Dielectric Hybrid Elliptical Waveguide

**MECHANICAL SPECIFICATIONS**

<b>Cable Size</b>		1/2
<b>Number of Cable / Waveguide Runs</b>		1
<b>Material</b>		Stainless Steel

**TEMPERATURE SPECIFICATIONS**

<b>Operation Temperature</b>	°C (°F)	-50 to 85 (-58 to 185 )
<b>Storage Temperature</b>	°C (°F)	-50 to 85 (-58 to 185 )

**PACKAGING INFORMATION**

<b>Package Quantity</b>		10
-------------------------	--	----

[External Document Links](#)

[Notes](#)