

Universal clamp with clamp lining for FLEXWELL® Elliptical Waveguide E78

The set consists of a hot dip galvanized universal clamp and a rubber clamp lining for $\mathsf{FLEXWELL}^{@}$ Elliptical Waveguide E78

FEATURES / BENEFITS

Easy waveguide installation

- The universal clamp with clamp lining is used for proper and secure installation of elliptical waveguides
- A suitable rubber inlet is included



| External Document Links | | Notes |
|-------------------------------------|---------|--|
| Technical features | | |
| GENERAL SPECIFICATIONS | | |
| Product Line | | Elliptical Waveguide Accessories |
| Product Type | | Hanger |
| Hanger Type | | Basic clamp with clamp lining |
| Transmission Line Type | | E78 EP78 |
| MECHANICAL SPECIFICATIONS | | |
| Number of Cable / Waveguide Runs | | 1 |
| Material | | Clamp: Hot dip galvanized steel Clamp Lining: EPDM rubber |
| TEMPERATURE SPECIFICATIONS | | |
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| PACKAGING INFORMATION | | |
| Package Quantity | | 10 |

CLAMP-R-078-E REV : A REV DATE : 01 Dec 2008 www.rfsworld.com