



Hangers for the installation of HELIFLEX<sup>®</sup> cables on different supporting profiles.

Cable Clamp and Extended Counterbed hot-galvanized steel

Screw: stainless steel.

#### FEATURES / BENEFITS



picture shows the 1L4 version  
for illustration purpose only

#### External Document Links

#### Notes

Hangers for angle iron 40mm (1.575")

## Technical features

### GENERAL SPECIFICATIONS

|                        |  |                           |
|------------------------|--|---------------------------|
| Product Line           |  | Coaxial Cable Accessories |
| Product Type           |  | Hanger                    |
| Hanger Type            |  | Angle iron 40mm (1.575")  |
| Transmission Line Type |  | HCA300                    |
| Cable Type             |  | Air Dielectric            |

### MECHANICAL SPECIFICATIONS

|  |        |  |
|--|--------|--|
| Cable Size                             |        | 3  |
| Material                               |        | Cable Clamp : hot-dip galvanized<br>Extended Counterbed : hot-dip galvanized<br>Screw: Stainless steel |
| Recommended / Maximum<br>Clamp Spacing | m (ft) | 0.8 / 1.2 (2.75 / 4)   |

### TEMPERATURE SPECIFICATIONS

|                       |         |                         |
|-----------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185 ) |
| Storage Temperature   | °C (°F) | -50 to 85 (-58 to 185 ) |

### PACKAGING INFORMATION

|                  |         |             |
|------------------|---------|-------------|
| Package Quantity |         | 1           |
| Weight per piece | kg (lb) | 0.51 (1.12) |