



CELLFLEX® 3/8" low loss flexible cable

**FEATURES / BENEFITS**

• **Ultra Low Attenuation**

The reduced attenuation of CELLFLEX® coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.

• **Complete Shielding**

The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.

• **Low VSWR**

Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.

• **Outstanding Intermodulation Performance**

CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.

• **High Power Rating**

Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.

• **Wide Range of Application**

Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects



**Technical features**

**INFORMATION**

<b>Applications</b>	OEM jumpers, BTS inter-cabinet connections, GPS lines, Microwave IF cabling, intended for outdoor usage
---------------------	---

**STRUCTURE**

<b>Size</b>		3/8
<b>Inner Conductor Diameter</b>	mm (in)	3.1 (0.122)
<b>Inner Conductor Material</b>		Copper-Clad Aluminum Wire
<b>Dielectric Diameter</b>	mm (in)	7.2 (0.283)
<b>Dielectric Material</b>		Foam Polyethylene
<b>Outer Conductor Diameter</b>	mm (in)	9.5 (0.374)
<b>Outer Conductor Material</b>		Corrugated Copper
<b>Jacket Diameter</b>	mm (in)	11.2 (0.441)
<b>Jacket Material</b>		Black Polyethylene

**TESTING AND ENVIRONMENTAL**

<b>Phase Stabilized</b>		Phase stabilized and phase matched cables and accessories are available upon request.
<b>Compliance</b>		DIN EN ISO 9001:2015 ISO 14001:2015 RoHS 2011/65/EU - China RoHS SJ/T 11364-2006 REACH (EC 1907/2006) UL1581 - UV Resistance Jacket IEC 60754-1/-2
<b>Installation Temperature</b>	°C(°F)	-40 to 60 (-40 to 140)
<b>Storage Temperature</b>	°C (°F)	-70 to 85 (-94 to 185)
<b>Operation Temperature</b>	°C(°F)	-50 to 85 (-58 to 185)



**ELECTRICAL SPECIFICATIONS**

Impedance	Ω	50 +/- 1.5
Maximum Frequency	GHz	13.5
Velocity	%	88
Capacitance	pF/m (pF/ft)	76 (23.2)
Inductance	uH/m (uH/ft)	0.19 (0.058)
Peak Power Rating	kW	15.4
RF Peak Voltage	Volts	1240
Jacket Spark	Volt RMS	5000
Inner Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	3.8 (1.16)
Outer Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	2.9 (0.88)
Passive Intermodulation PIM	min. dBc	-160
Return Loss (VSWR) Performance	Standard 20dB (1.222) / Premium 23/24dB (1.152/1.135) on specified frequencies	

**MECHANICAL SPECIFICATIONS**

Cable Weight, Nominal	kg/m (lb/ft)	0.13 (0.087)
Minimum Bending Radius, Single Bend	mm (in)	50 (2)
Minimum Bending Radius, Repeated Bends	mm (in)	95 (4)
Bending Moment	Nm (lb-ft)	1.9 (1.4)
Tensile Strength	N (lb)	530 (119)
Recommended / Maximum Clamp Spacing	m (ft)	0.5 / 1 (1.75 / 3.25)

**ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)**

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
1	0.34	0.1	21.59
100	3.43	1.04	2.12
200	4.89	1.49	1.48
450	7.44	2.27	0.97
700	9.38	2.86	0.77
800	10.06	3.07	0.72
900	10.71	3.27	0.68
1800	15.54	4.74	0.47
2000	16.45	5.01	0.44
2200	17.33	5.28	0.42
2400	18.17	5.54	0.40
2700	19.39	5.91	0.37
3000	20.55	6.26	0.35
3500	22.39	6.82	0.32



4000	24.12	7.35	0.3
5000	27.35	8.34	0.27
13500	48.8	14.88	0.15

**RELATED PRODUCTS**

Connector Interface	Premium Connector Series E01	Connector Series 070 / 071
N Male	<a href="#">NM-LCF38-E01</a>	<a href="#">NM-LCF38-070</a>
N Female	<a href="#">NF-LCF38-E01</a>	<a href="#">NF-LCF38-070</a>
4.3-10 Male	<a href="#">43M-LCF38-E01</a>	
<b>Mandatory Tool</b>		<a href="#">TRIM-38-L03</a>
<b>Tool Information</b>		Trimming Tool For *-070 And *-071 Connector Series
<b>Installation Video</b>		
<b>General Accessories</b>		
<b>Hand Tool Kit</b>		<a href="#">TRIM-T01</a>
<b>Grounding Kit</b>		<a href="#">EAR-38-L</a>

External Document Links

[CELLFLEX Drum Selection Guide](#)

Notes