



Double Multi block hanger support systems are designed for organizing bundled runs of coax cable.

Each space-saving block securely holds two runs of coax, allowing a compact bundle of up to 6x runs to be supported by stacking three blocks.

**FEATURES / BENEFITS**

MBH114-6-F for illustration purpose

**External Document Links**[Installation Instruction](#)**Notes****Technical features****GENERAL SPECIFICATIONS**

Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Single Multi-block
Transmission Line Type		LCF12 HCA12-50
Color		Black

**MECHANICAL SPECIFICATIONS**

Cable Size		1/2
Number of Cable / Waveguide Runs		2 per layer, 3 layer, 6 runs
Configuration		incl. Angle member adapter
Angle member adapter clamping range mm (in)		4 / 24 (0.157 / 0.945 )
Angle member adapter threads		2x M8
Material		Metal parts: -Connecting devices:Stainless steel -Angle member adapter: Stainless steel -Plastic parts: Polypropylene
Length	mm (in)	190 (7.48)
Height	mm (in)	58 (2.28)
Width	mm (in)	50 (1.96)
Recommended / Maximum Clamp Spacing	m (ft)	0.6 / 1 (2 / 3.25)

**TEMPERATURE SPECIFICATIONS**

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185 )

**PACKAGING INFORMATION**

Package Quantity		10
Weight per piece	kg (lb)	0.263 (0.58)
Weight per kit	kg (lb)	2.65 (5.8)



## MBH12-6-F

Double Multi-block hanger three layers, with angle member adapter



picture shows MBH114-6-F for illustration purpose