



Double Multi block hanger support systems are designed for organizing bundled runs of coax cable. Each space-saving block securely holds two runs of coax, allowing a compact bundle of up to 6x runs to be supported by stacking three blocks.

FEATURES / BENEFITS



MBH114-6-F for illustration purpose

Technical features

GENERAL SPECIFICATIONS

Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Single Multi-block
Transmission Line Type		UCF78 LCF78
Color		Black

MECHANICAL SPECIFICATIONS

Cable Size		7/8
Number of Cable / Waveguide Runs		2 per layer, 3 layers, 6 runs
Configuration		incl. Angle member adapter
Angle member adapter clamping range mm (in)		4 / 24 (0.157 / 0.945)
Angle member adapter threads		2x M8
Material		Metal parts: -Connecting devices:Stainless steel -Angle member adapter: Stainless steel -Plastic parts: Polypropylene
Length	mm (in)	245 (9.65)
Height	mm (in)	85 (3.35)
Width	mm (in)	50 (1.96)
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1 (2.75 / 3.25)

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity		10
Weight per piece	kg (lb)	0.364 (0.8)
Weight per kit	kg (lb)	3.65 (8)



picture shows MBH114-6-F for illustration purpose

[External Document Links](#)

[Installation Instruction](#)

[Notes](#)