



Twistable and flexible rectangular waveguide R140, with PBR/UBR 140 flanges. Length = 0.9m, core with environmental impact resistant molded rubber jacket. Hardware and gasket (for PDR/PBR flanges) included.

FEATURES / BENEFITS

Waveguide installation

- The flexible and twistable rectangular waveguide component eliminates installation difficulties
- It isolates vibration
- It provides simple aid to positioning of antennas

**Technical features****STRUCTURE**

Type of Rectangular Waveguide Component		TwistFlex
Waveguide Size IEC (EIA)		R140 (WR62)
Flange A		PBR140
Flange B		UBR140
Flange Finish		Brass un-plated
Package Quantity		1

ELECTRICAL SPECIFICATIONS

Frequency Range	GHz	11.9 - 18
Minimum Return Loss (max. VSWR)	dB (VSWR)	24.9 (1.12)
Attenuation	dB	0.72
Power rating	W	400

MECHANICAL SPECIFICATIONS

Maximum Twist	degree/m (degree/ft)	250 (76)
Minimum Bending Radius E-Plane	mm (in)	25 (1)
Minimum Bending Radius H-Plane	mm (in)	47 (1.9)
Length	mm (in)	900 (35.4)
Weight	kg (lb)	0.46 (0)

MATERIAL

Material		Core: Brass silver plated Jacket: Rubber Silicone Flange: Brass
Color		Black

External Document Links

[AN 030707-8 Application note for RFS Twistflex](#)

Notes