



These innovative Wall feed through systems feature a design which reduces installation time. Each WF-Kit contains a rubber wall gland which fits inside the mounting plate to hold the coax in place, a butyl sealing compound and a tension clamp with two bolts.

**FEATURES / BENEFITS**



[External Document Links](#)

[Notes](#)

[Installation Instruction](#)

**Technical features**

**STRUCTURE**

|                               |  |                               |                 |
|-------------------------------|--|-------------------------------|-----------------|
| <b>Product Line</b>           |  | Coaxial Cable Accessories     |                 |
| <b>Product Type</b>           |  | Wall/Roof Feed-Through System |                 |
| <b>Feed-Through Component</b> |  | Single Entry Kit              |                 |
| <b>Transmission Line Type</b> |  | HCA38                         |                 |
| <b>Coaxial Cable Type</b>     |  | Air Dielectric                | Foam Dielectric |
| <b>Cable Size</b>             |  | 3/8"                          |                 |

**MECHANICAL SPECIFICATIONS**

|  |         |           |  |
|--|---------|-----------|--|
| <b>Feed-Through Holes</b>                |         | 1         |  |
| <b>Feed-Through Hole Diameter</b>        | mm (in) | 40 (1.58) |  |
| <b>Mated to Cable Size and Interface</b> |         | 3/8       |  |

**PACKAGING INFORMATION**

|                         |  |   |  |
|-------------------------|--|---|--|
| <b>Package Quantity</b> |  | 1 |  |
|-------------------------|--|---|--|