



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions.

FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



OMNI FIT™ Standard Connectors

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type	Coaxial Cable		
Cable Size	1 5/8		
Cable Type	Foam Dielectric	Radiating	
Model Series	LCF158-50 Series	RCF158-50 Series	
Connector Interface	7-16 DIN		
Connector Type	OMNI FIT™ Standard		
Sealing Method	O-ring		
Gender	Female		

ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50	
3rd Order IM Product @ 2x20 Watts	dBc	-159 typical	
Maximum Frequency	GHz	2.75	
VSWR, Return Loss	VSWR (dB)	0 < f=1.0 GHz: 1.03 (36.6) 1.0 < f=2.2 GHz: 1.04 (34.1)	

MECHANICAL SPECIFICATIONS

Plating Outer/Inner	Trimetal/Silver		
Length	mm (in)	64.6 (2.54)	
Outer Diameter	mm (in)	62.9 (2.5)	
Inner Contact Attachment	Spring Finger		
Outer Contact Attachment	Spring C-Ring		


ACCESSORIES

Wrench size front	mm (in)	Open end wrench 55 (2-1/6)	
Wrench size rear	mm (in)	Open end wrench 60 (2-1/3)	
Poly Hook Spanner	mm (in)	PHS 60-90-5 Ø 60-90 (2.3-3.5) Pin 5 (0.2)	



TESTING AND ENVIRONMENTAL

Waterproof Level		IP68
-------------------------	--	------



External Document Links

- [Application Note](#)
- [Installation Instruction](#)

Notes