
Coaxial Adapter 7-16 Female - 4.3-10 Female with right angle FEATURES / BENEFITS



Technical features

STRUCTURE

Product Line	Coaxial Cable Components
Product Type	Coaxial Adapter

MECHANICAL SPECIFICATIONS

Connector A	7-16 Female
Center Contact Connector A	Phosphor Bronze, silver plated
Outer Contact Connector A	Brass, Tri metal alloy plated
Connector B	4.3-10 Female
Center Contact Connector B	Phosphor Bronze, silver plated
Outer Contact Connector B	Brass, Tri metal alloy plated
Dielectric	PTFE
Sealing class	IP68, connected

ELECTRICAL SPECIFICATIONS

Frequency Range - MHz		DC - 6000	
VSWR, Return Loss	VSWR (dB)	DC TO 2 GHz VSWR 1.05 (32.25) 2 TO 3 GHz VSWR 1.08 (28.3) 3 TO 6 GHz VSWR 1.12 (24.94)	
Insertion Loss, dB (Max)	dB	0.05	
3rd Order IM Product @ 2x20 Watts	dBc	-163	

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-40 to 85 (-40 to 185)

PACKAGING INFORMATION

Backago Quantity		1	
Package Quantity		I	

External Document Links

Notes

716F-R-43F REV : B REV DATE : 19 Apr 2023 **www.rfsworld.com**