



**B320-380FP**

Connector for FLEXWELL® elliptical waveguide E380, PBR320 Flange

Standard connector for FLEXWELL® elliptical waveguide E380 with PBR320 flange, gasket with shrinking sleeve sealed  
frequency range: 37.0 - 39.5 GHz

**FEATURES / BENEFITS**

**Superior Design**

- Due to the precise manufacturing no tuning screws are necessary
- The terminations are brass passivated for good electrical performance
- A gas inlet is included
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



**Quick & Easy Installation**

- Different flaring tools are available
- No tuning in the field

**Technical features**

**STRUCTURE**

Transmission Line Type		Elliptical Waveguide
Cable Type		E380
Model Series		E380 Series
Connector Frequency Range	GHz	37 - 39.5
Connector Type		Fixed
Sealing Method		Gasket with Shrinking Sleeve
Plating Outer/Inner		Brass
Waterproof Level		IP68
Gas Inlet		M5 x 0.8
Connector Interface		PBR320

**MECHANICAL SPECIFICATIONS**

Length	mm (in)	52 (2)
Outer Diameter	mm (in)	30 (1.2)
Weight	kg (lb)	0.2 (0.44)

**External Document Links**

- [Installation Instruction](#)
- [Application Note](#)

**Notes**