Hanger, non-insulated, bolt-on for elliptical waveguides E46 / ES46 / EP46 / ESP46, made of stainless steel

## FEATURES / BENEFITS

**Package Quantity** 

Stainless steel hangers for supporting elliptical waveguide to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



| External Document Links             |         | Notes                            |
|-------------------------------------|---------|----------------------------------|
| Technical features                  |         |                                  |
| GENERAL SPECIFICATIONS              |         |                                  |
| Product Line                        |         | Elliptical Waveguide Accessories |
| Product Type                        |         | Hanger                           |
| Hanger Type                         |         | Bolt-On, non-insulated           |
| Transmission Line Type              |         | ES46<br>ESP46<br>E46<br>EP46     |
| MECHANICAL SPECIFICATIONS           |         |                                  |
| Number of Cable / Waveguide<br>Runs |         | 1                                |
| Material                            |         | Stainless Steel                  |
| TEMPERATURE SPECIFICATIONS          |         |                                  |
| Operation Temperature               | °C (°F) | -50 to 85 (-58 to 185 )          |
| Storage Temperature                 | °C (°F) | -50 to 85 (-58 to 185 )          |
| PACKAGING INFORMATION               |         |                                  |

10

CLAMP-046 REV : D REV DATE : 13 Jul 2023 www.rfsworld.com