

Cable hanger, non-insulated, bolt-on, for 7/8" coaxial cable and E100, E105 elliptical waveguide

Hanger, non-insulated, bolt-on for coaxial cable LCF78 / UCF78 / RCF78 / HCA78 and for eliptical waveguide EP100/E105/EP105 made of stainless steel

FEATURES / BENEFITS

Stainless steel hangers for supporting elliptical waveguide to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



External Document Links Notes

Technical features

GENERAL SPECIFICATIONS

Product Line		Coaxial Cable Accessories Radiating Cable Accessories
		Elliptical Waveguide Accessories Hybrid Cable Accessories
Product Type		Hanger
Hanger Type		Bolt-On, non-insulated
Transmission Line Type		LCF78
		UCF78
		RCF78
		EP100
		E105
		EP105
		HB078
		HCA78
Cable Type		Coaxial Foam Dielectric
		Radiating Cable
		Hybrid
MECHANICAL SPECIFICATIONS		
Cable Size		7/8
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
TEMPERATURE SPECIFICATIONS		
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity	10

CLAMP-100/105 REV : A REV DATE : 11 Jun 2024 www.rfsworld.com