



**CLAMP-114**

Cable hanger, non-insulated, bolt-on, for 1 1/4" coaxial cable and elliptical waveguide E65 and E70

Hanger, non-insulated, bolt-on for coaxial cable  
LCF114 / LCFS114 / RCF114  
and for elliptical waveguide E65/EP65 and E70/EP70  
made of stainless steel, kit of 10

**FEATURES / BENEFITS**

Stainless steel hangers for supporting elliptical waveguide or coaxial cable to tower.  
Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs,  
member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters  
through slot



**Technical features**

**GENERAL SPECIFICATIONS**

|                               |  |  |
|-------------------------------|--|--|
| <b>Product Line</b>           |  | Coaxial Cable Accessories<br>Radiating Cable Accessories<br>Elliptical Waveguide Accessories<br>Hybrid Cable Accessories |
| <b>Product Type</b>           |  | Hanger   |
| <b>Hanger Type</b>            |  | Bolt-On, non-insulated   |
| <b>Transmission Line Type</b> |  | LCF114<br>LCFS114<br>RCF114<br>UCF114<br>E65<br>EP65<br>E70<br>EP70<br>HB114   |
| <b>Cable Type</b>             |  | Coaxial Foam Dielectric<br>Radiating Cable<br>Hybrid   |

**MECHANICAL SPECIFICATIONS**

|   |  |                 |
|---|--|-----------------|
| <b>Cable Size</b>                       |  | 1-1/4           |
| <b>Number of Cable / Waveguide Runs</b> |  | 1               |
| <b>Material</b>                         |  | Stainless Steel |

**TEMPERATURE SPECIFICATIONS**

|                              |         |                         |
|------------------------------|---------|-------------------------|
| <b>Operation Temperature</b> | °C (°F) | -50 to 85 (-58 to 185 ) |
| <b>Storage Temperature</b>   | °C (°F) | -50 to 85 (-58 to 185 ) |

**PACKAGING INFORMATION**

|                         |  |    |
|-------------------------|--|----|
| <b>Package Quantity</b> |  | 10 |
|-------------------------|--|----|

[External Document Links](#)

[Notes](#)