



**CLAMP-158-S**

Cable hanger, non-insulated, bolt-on, for 1 5/8" coaxial cable

Hanger, non-insulated, bolt-on for coaxial cable LCF158 and HCA158 and as fire resistance support for RCF158 and all RADIAFLEX® 1 5/8" with copper foil as outer conductor.  
Made of stainless steel, kit of 10

**FEATURES / BENEFITS**

- Stainless steel hangers for supporting coaxial cable to tower.
  - Member mounting holes with up to M10 or 3/8"-16 hardware.
  - Hanger may be attached to angle adapters, tower standoffs.
  - Hanger may be attached to round member adapters through slot.
  - Installation every 10m (30ft) as fire resistance support for RADIAFLEX®. Keep's the RADIAFLEX® cable in position during fire impact to prevent potential blocking of escape path.
- All installation components should be made of stainless steel.



**Technical features**

**GENERAL SPECIFICATIONS**

Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Bolt-On, non-insulated
Transmission Line Type		LCF158, HCA158, RCF158 RLF*, RLK*, RAY*, RLV*
Cable Type		Coaxial Foam Dielectric Air Dielectric

**MECHANICAL SPECIFICATIONS**

Cable Size		1-5/8
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1.2 (2.75 / 4)

**TEMPERATURE SPECIFICATIONS**

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185 )

**PACKAGING INFORMATION**

Package Quantity		10
------------------	--	----

**External Document Links**

**Notes**

If using the Bolt-on hanger series in vertical runs, the hoisting grips need to be kept on the tower.  
\* Valid for all 1 5/8" types