



CLAMP-214

Cable hanger, non-insulated, bolt-on, for 2 1/4" coaxial cable

Hanger, non-insulated, bolt-on for coaxial cable
LCF214, made of stainless steel, kit of 10

FEATURES / BENEFITS

Stainless steel hangers for supporting elliptical waveguide or coaxial cable to tower.
Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



Technical features

GENERAL SPECIFICATIONS

| | | |
|------------------------|--|-------------------------------------------|
| Product Line | | Coaxial Cable Accessories |
| Product Type | | Hanger |
| Hanger Type | | Bolt-On, non-insulated |
| Transmission Line Type | | LCF214 |
| Cable Type | | Air Dielectric Coaxial Foam Dielectric |

MECHANICAL SPECIFICATIONS

| | | |
|-------------------------------------|--------|----------------------|
| Cable Size | | 2-1/4 |
| Number of Cable / Waveguide Runs | | 1 |
| Material | | Stainless Steel |
| Recommended / Maximum Clamp Spacing | m (ft) | 0.8 / 1.2 (2.75 / 4) |

TEMPERATURE SPECIFICATIONS

| | | |
|-----------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |

PACKAGING INFORMATION

| | | |
|------------------|--|----|
| Package Quantity | | 10 |
|------------------|--|----|

External Document Links

Notes

If using the Bolt-on hanger series in vertical runs, the hoisting grips need to be kept on the tower.