Hanger, non-insulated, bolt-on for coaxial cable

HCA300, made of stainless steel

FEATURES / BENEFITS

Stainless steel hangers for supporting coaxial cable to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



ı		Clamp for 1-5/8" snown as a sample
l	External Document Links	Notes
l		If using the Bolt-on hanger series in vertical runs, the hoisting grips
l		need to be kept on the tower.
н		

Technical features

GENERAL S	PECIFI	CATIONS
------------------	--------	---------

Product Line	Coaxial Cable Accessories
Product Type	Hanger
Hanger Type	Bolt-On, non-insulated
Transmission Line Type	HCA300
Cable Type	Air Dielectric

MECHANICAL SPECIFICATIONS

Cable Size		3"
Number of Cable / Waveguide Runs		1
Material		Stainless Steel
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1.2 (2.75 / 4)

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity	10

www.rfsworld.com CLAMP-300-S REV: C REV DATE: 13 Jul 2023