



Standard connector for FLEXWELL® elliptical waveguide E78 with PDR84 flange, gasket with shrinking sleeve sealed
frequency range: 7.1 - 8.5 GHz

FEATURES / BENEFITS**Superior Design**

- Due to the precise manufacturing no tuning screws are necessary
- The terminations are brass passivated for good electrical performance
- A gas inlet is included
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

**Quick & Easy Installation**

- Different flaring tools are available
- No tuning in the field

Technical features**STRUCTURE**

Transmission Line Type		Elliptical Waveguide
Cable Type		E78
Model Series		E78 Series
Connector Frequency Range	GHz	7.1 - 8.5
Connector Type		Fixed
Sealing Method		Gasket
Plating Outer/Inner		Brass
Waterproof Level		IP68
Gas Inlet		G 1/8
Connector Interface		PDR84

MECHANICAL SPECIFICATIONS

Length	mm (in)	112 (4.4)
Outer Diameter	mm (in)	60 (2.4)
Weight	kg (lb)	1.7 (3.75)

External Document Links[Installation Instruction](#)[1000009163-01_Application Note_Installation of Heat Shrink Sleeves for additional sealing of Connectors.pdf](#)**Notes**