




A simplex fiber optic patch cord incorporating bend insensitive single mode fiber, preterminated with SC/APC connectors on both ends. The tight buffered fibre and non metallic strain member is protected by an LSZH jacket, suitable for indoor applications

#### FEATURES / BENEFITS

- High precision SC/APC connector provides low insertion loss, high return loss, excellent stability, repeatability and durability
- All connectors are terminated and fully tested in controlled conditions to ensure optimum performance and reliability
- Available in a range of standard or customized lengths to simplify network design



Fiber Optical Patch Cord, (U) SC/APC, (U) SC/APC, 1 core Fiber, Simplex Fiber, Single Mode, XXX Meters

[External Document Links](#)

[Notes](#)

## Technical features

#### STRUCTURE

Cable Type		Tight buffered optical fiber
Number of Fiber		1

#### MECHANICAL SPECIFICATIONS

Minimum Bending Radius, (Operating)	mm (in)	20 (0.787)
Minimum Bending Radius, (Installation)	mm (in)	40 (1.575)
Tensile Strength (Operating)		40 N
Tensile Strength (Installation)		80 N
Crush Resistance (Operating)		100 N / 10 cm
Crush Resistance (Installation)		500 N / 10 cm

#### CABLE JACKET

Jacket Material		Yellow LSZH
Outer Diameter Nominal	mm (in)	2 (0.079)

#### F/O CABLE SPECIFICATIONS

F/O Cable Type		Tight Buffer, Single Mode
Core/Clad	μm	9 /125
F/O Cable Jacket		Yellow LSZH
F/O Standards (Meets or Exceeds)		ITU G 657.A2
Fiber Termination End 1		SC/APC, simplex, single mode, IEC 61754-4
Fiber Termination End 2		SC/APC, simplex, single mode, IEC 61754-4
Fiber Attenuation	dB/km	≤ 0.36dB/km λ=1310nm ; ≤0.22dB/km λ =1550nm
Connector Insertion Loss		Max. 0.30 dB @ 1310&1550nm@IEC 61300-3-4 Method B
Connector Return Loss		Min. 60 dB @ 1310&1550nm@IEC 61300-3-6

#### TESTING AND ENVIRONMENTAL

Storage Temperature	°C (°F)	-25 to 70 (-13 to 158 )
Operation Temperature	°C (°F)	-20 to 60 (-4 to 140 )
Installation Temperature	°C (°F)	-5 to 50 (23 to 122 )




FOPC-UU1SS-XXXM

Fiber Optic Patch Cord, Simplex, SC/APC to SC/APC, Single Mode, LSZH, Indoor

ADDITIONAL ASSEMBLIES

Length	Model Name
1 m	FOPC-UU1SS-001M
2 m	FOPC-UU1SS-002M
3 m	FOPC-UU1SS-003M
4 m	FOPC-UU1SS-004M
5 m	FOPC-UU1SS-005M
6 m	FOPC-UU1SS-006M
7 m	FOPC-UU1SS-007M
8 m	FOPC-UU1SS-008M
9 m	FOPC-UU1SS-009M
10 m	FOPC-UU1SS-010M



Side  
A

Side  
B

