




**PRODUCT DESCRIPTION**

RFS' HYBRIFLEX Remote Radio Head (RRH) hybrid feeder cabling solution combines any combination of optical fiber and/or DC power for RRHs in a single lightweight armored or unarmored cable, making it the world's most innovative solution for RRH deployments. Hybrid, Fiber Optic and DC riser trunk and jumper cables are available in a large variety of fiber counts, DC counts and cross sections. Both pre-connectorized and on-site options are available.



**FEATURES / BENEFITS**

- Ruggedized, bend-insensitive fiber design with outstanding bending characteristics
- Lightweight solution and compact design – Decreases tower loading
- Robust cabling – Eliminates need for expensive cable trays and ducts
- Installation of tight bundled fiber optic cable pair directly to the RRH – Reduces CAPEX and wind load by eliminating need for interconnection
- Outdoor, black jacket – Ensures long-lasting cable protection
- **100% Factory tested - Online test results available**

**TECHNICAL FEATURES**

**STRUCTURE**

|                  |        |                 |
|------------------|--------|-----------------|
| Cable Type       |        | HYBRIFLEX®      |
| Fire Performance |        | Flame Retardant |
| Length           | m (ft) | 0.3 (1)         |

**MECHANICAL SPECIFICATIONS**

|  |              |                    |
|--|--------------|--------------------|
| Outer Diameter Nominal                 | mm (in)      | 5.5 (0.217)        |
| Cable Weight                           | kg/m (lb/ft) | 0.033 (0.022)      |
| Minimum Bending Radius, Single Bend    | mm (in)      | 66 (2.6)           |
| Minimum Bending Radius, Multiple Bends | mm (in)      | 83 (3.3)           |
| Recommended / Maximum Clamp Spacing    | m (ft)       | 1 / 1.2 (3.25 / 4) |

**F/O CABLE SPECIFICATIONS**

|                                  |         |   |
|----------------------------------|---------|---|
| Number of F/O Pairs              |         | 1   |
| F/O Cable Type                   |         | G657-A2 Single Mode, Bend Tolerant                            |
| Core/Clad                        | µm      | 9/125   |
| Secondary Protection Nominal     | µm (in) | 900 (0.035)   |
| F/O Standards (Meets or Exceeds) |         | UL Listed Type OFNR (UL1666), RoHS Compliant                  |
| Optical Loss                     | dB/Km   | 0.5 @ 1310 nm<br>0.5 @ 1550 nm                                |
| FO Break-out Length (Top)        | mm (in) | 279 (11)  |
| FO Break-out Length (Bottom)     | mm (in) | 228 (9)   |
| Cable Sealing Method             |         | Semi-rigid flame-retardant polyolefin, with hot melt adhesive |
| Fiber Termination End 1          |         | DLC Connector   |
| Fiber Termination End 2          |         | DLC Connector   |



**CABLE JACKET**

|  |  |   |
|--|--|---|
| UV-Protection Individual and External Jacket |  | Yes   |
| Jacket Material                              |  | Flame Retardant, Indoor/Outdoor, PVC, Black |

**TESTING AND ENVIRONMENTAL**

|                          |         |                        |
|--------------------------|---------|------------------------|
| Storage Temperature      | °C (°F) | -40 to 70 (-40 to 158) |
| Operation Temperature    | °C (°F) | -40 to 65 (-40 to 149) |
| Installation Temperature | °C (°F) | -20 to 65 (-4 to 149)  |
| Jacket Specifications    |         | UL 1666                |

**EXTERNAL DOCUMENT LINKS**

Installation Guidelines: [Download](#)

QuickShip 2.0 Program Information: [Download](#)

On-line Factory Test Results: [View](#)

**NOTES**



**ADDITIONAL ASSEMBLIES - 1 PAIR SM FIBER**

| Length, ft | Model Number     |
|------------|------------------|
| 6          | FR-N-1SM-01-6F   |
| 10         | FR-N-1SM-01-10F  |
| 15         | FR-N-1SM-01-15F  |
| 20         | FR-N-1SM-01-20F  |
| 30         | FR-N-1SM-01-30F  |
| 40         | FR-N-1SM-01-40F  |
| 50         | FR-N-1SM-01-50F  |
| 60         | FR-N-1SM-01-60F  |
| 79         | FR-N-1SM-01-70F  |
| 80         | FR-N-1SM-01-80F  |
| 90         | FR-N-1SM-01-90F  |
| 100        | FR-N-1SM-01-100F |

**ADDITIONAL ASSEMBLIES - 2 PAIR SM FIBER**

| Length, ft | Model Number     |
|------------|------------------|
| 10         | FR-N-2SM-01-10F  |
| 20         | FR-N-2SM-01-20F  |
| 30         | FR-N-2SM-01-30F  |
| 40         | FR-N-2SM-01-40F  |
| 50         | FR-N-2SM-01-50F  |
| 60         | FR-N-2SM-01-60F  |
| 70         | FR-N-2SM-01-70F  |
| 80         | FR-N-2SM-01-80F  |
| 90         | FR-N-2SM-01-90F  |
| 100        | FR-N-2SM-01-100F |



**FR-N-1SM-01-1F**

HYBRIFLEX® RRH Optical Fiber Cable, 1 Pair, Ruggedized Bend-Insensitive Single-Mode Fiber, DLC Connectors, 1 ft

**ADDITIONAL ASSEMBLIES - 3 PAIR SM FIBER**

| Length, ft | Model Number    |
|------------|-----------------|
| 3          | FR-N-3SM-01-3F  |
| 4          | FR-N-3SM-01-4F  |
| 6          | FR-N-3SM-01-6F  |
| 8          | FR-N-3SM-01-8F  |
| 10         | FR-N-3SM-01-10F |
| 15         | FR-N-3SM-01-15F |
| 20         | FR-N-3SM-01-20F |
| 30         | FR-N-3SM-01-30F |
| 50         | FR-N-3SM-01-50F |

**ADDITIONAL ASSEMBLIES - 6 PAIR SM FIBER**

| Length, ft | Model Number    |
|------------|-----------------|
| 3          | FR-N-6SM-01-3F  |
| 4          | FR-N-6SM-01-4F  |
| 6          | FR-N-6SM-01-6F  |
| 8          | FR-N-6SM-01-8F  |
| 10         | FR-N-6SM-01-10F |
| 15         | FR-N-6SM-01-15F |
| 20         | FR-N-6SM-01-20F |
| 30         | FR-N-6SM-01-30F |
| 40         | FR-N-6SM-01-40F |

**ADDITIONAL ASSEMBLIES - 12 PAIR SM FIBER**

| Length, ft | Model Number     |
|------------|------------------|
| 3          | FR-N-12SM-01-3F  |
| 4          | FR-N-12SM-01-4F  |
| 6          | FR-N-12SM-01-6F  |
| 8          | FR-N-12SM-01-8F  |
| 10         | FR-N-12SM-01-10F |
| 15         | FR-N-12SM-01-15F |
| 20         | FR-N-12SM-01-20F |
| 30         | FR-N-12SM-01-30F |

**ADDITIONAL ASSEMBLIES - 1 STRAND SM FIBER**

| Length, ft | Model Number      |
|------------|-------------------|
| 10         | FR-N-1SSM-01-10F  |
| 20         | FR-N-1SSM-01-20F  |
| 30         | FR-N-1SSM-01-30F  |
| 40         | FR-N-1SSM-01-40F  |
| 50         | FR-N-1SSM-01-50F  |
| 60         | FR-N-1SSM-01-60F  |
| 70         | FR-N-1SSM-01-70F  |
| 80         | FR-N-1SSM-01-80F  |
| 90         | FR-N-1SSM-01-90F  |
| 100        | FR-N-1SSM-01-100F |

**ADDITIONAL ASSEMBLIES - 2 STRAND SM FIBER**

| Length, ft | Model Number      |
|------------|-------------------|
| 10         | FR-N-2SSM-01-10F  |
| 20         | FR-N-2SSM-01-20F  |
| 30         | FR-N-2SSM-01-30F  |
| 40         | FR-N-2SSM-01-40F  |
| 50         | FR-N-2SSM-01-50F  |
| 60         | FR-N-2SSM-01-60F  |
| 70         | FR-N-2SSM-01-70F  |
| 80         | FR-N-2SSM-01-80F  |
| 90         | FR-N-2SSM-01-90F  |
| 100        | FR-N-2SSM-01-100F |