

**HA-DCPLUG-LI-xx Series****HYBRIFLEX® DC Connector Splitter for Low Inductance, Concentric Power Wire Kit**

RFS' patented DC wire insulator. Specially designed for Low Inductance, coaxial/concentric, DC wire installation in junction boxes and other applications. Allows for consistent and safe termination of these special wire types in various types of terminal block connectors.

**FEATURES / BENEFITS**

- Avoids short circuits when using Low Inductance wire
- Made of flexible material for easier installation
- Included with many of the "LI" type HYBRIFLEX cables from RFS
- Also offered separately in multi-piece kits

[External Document Links](#)[Notes](#)[Installation Guidelines](#)**Technical features****GENERAL SPECIFICATIONS**

Product Type		Power Wire Splitter Connector
--------------	--	-------------------------------

**MECHANICAL SPECIFICATIONS**

Material		PVC
Weight	kg (lb)	0.003 (0.007)
Dimensions Power Connector (LxWxD)	mm (in)	13.6 x 15.4 x 51.9 (0.54 x 0.61 x 2.04)

**TESTING AND ENVIRONMENTAL**

Storage Temperature	°C (°F)	-40 to 75 (-40 to 167 )
Operation Temperature	°C (°F)	-40 to 75 (-40 to 167 )
Installation Temperature	°C (°F)	-40 to 75 (-40 to 167 )
UV-Protection		Yes

**ELECTRICAL SPECIFICATIONS**

Supported Wire Cross Section		6 AWG
------------------------------	--	-------

**ADDITIONAL INFORMATION**

Kit Model	Quantity Provided in Kit
HA-DCPLUG-LI-06	6
HA-DCPLUG-LI-14	14

## HA-DCPLUG-LI-xx Series

HYBRIFLEX® DC Connector Splitter for Low Inductance, Concentric Power Wire Kit

