



**RFS' HYBRIFLEX™** cabling solution for Remote Radio Head (RRU) combines optical fiber and DC power for RRUs in a single lightweight aluminum corrugated cable, making it the world's most innovative solution for RRH deployments. It was developed to reduce installation complexity and cost at Cellular sites.

**HYBRIFLEX™** cabling solutions allows mobile operators deploying RRH architecture to standardize RRH installation process and eliminates the need for and the cost of cable grounding. The FTTA Jumper is part of the cabling solution for RRU's meant to build the F/O connection from the Adapter to the RRU. The Jumper cables can be ordered in 1m, 2m, 3m, 4m, and 5m jacketed length.

**FEATURES / BENEFITS**

- **Outdoor polyethylene jacket** ð Ensure long-lasting cable protection
- **High class F/O performance**
- **IP 67 connector sealing**



External Document Links

Notes

**Technical features**

**STRUCTURE**

Cable Type		Fiber Jumper
Size		5 mm

**MECHANICAL SPECIFICATIONS**

Minimum Bending Radius, (Operating)	mm (in)	70 (3)
Minimum Bending Radius, (Installation)	mm (in)	125 (5)

**CABLE JACKET**

UV-Protection Individual and External Jacket		Yes
Outer Diameter Nominal	mm (in)	5 (0.18)

**F/O CABLE SPECIFICATIONS**

F/O Cable Type		Tight Buffer, Single Mode
Number of F/O Pairs		1
Core/Clad	µm	9 /125
Optical Loss	dB/Km	1 @ 1310 nm 1 @ 1550 nm
Fiber Termination End 1		ODVA Connector
Fiber Termination End 2		LC Connector

**TESTING AND ENVIRONMENTAL**

Storage Temperature	°C (°F)	-40 to 70 (-40 to 158 )
Operation Temperature	°C (°F)	-40 to 65 (-40 to 149 )
Installation Temperature	°C (°F)	-20 to 65 (-4 to 149 )

**ADDITIONAL ASSEMBLIES**

Length		Model Name
1 m		HA-FOJMP-VL-SM-01
2 m		HA-FOJMP-VL-SM-02



**HA-FOJMP-VL-SM-XX**

HYBRIFLEX® Fiber Jumper, Single-Mode Fiber Jumper

3 m	HA-FOJMP-VL-SM-03
4 m	HA-FOJMP-VL-SM-04
5 m	HA-FOJMP-VL-SM-05
6 m	HA-FOJMP-VL-SM-06
7 m	HA-FOJMP-VL-SM-07
8 m	HA-FOJMP-VL-SM-08
9 m	HA-FOJMP-VL-SM-09
10 m	HA-FOJMP-VL-SM-10
11 m	HA-FOJMP-VL-SM-11
12 m	HA-FOJMP-VL-SM-12
13 m	HA-FOJMP-VL-SM-13
14 m	HA-FOJMP-VL-SM-14
15 m	HA-FOJMP-VL-SM-15
16 m	HA-FOJMP-VL-SM-16
17 m	HA-FOJMP-VL-SM-17
18 m	HA-FOJMP-VL-SM-18
19 m	HA-FOJMP-VL-SM-19
20 m	HA-FOJMP-VL-SM-20

