



RFS' HYBRIFLEX™ cabling solution for Remote Radio Unit (RRU) combines optical fiber and DC power in a single lightweight aluminum corrugated cable, making it the world's most innovative solution for RRU deployments. It was developed to reduce installation complexity and cost at Cellular sites.

HYBRIFLEX™ cabling solutions allows mobile operators deploying RRU architecture to standardized installation process and eliminates the need and the cost for an internal grounding wire.

The HYBRIFLEX™ cable is part of a site installation kit. It consists of an armored bundle of 4 unshielded DC cables, 8 F/O distribution cables and a rip cord to adjust the breakout part of the cable.

**FEATURES / BENEFITS**

- A corrugated armor with excellent bending characteristics minimizes installation time and enables mechanical protection and EMC shielding
- Outer conductor grounding eliminates typical additional grounding requirement and saves on installation costs
- Lightweight solution and compact design decreases tower loads
- Robust cabling eliminates need for expensive cable trays and conduits
- Installation of stripped fiber optic cable pairs directly to RRH reduces CAPEX and wind load by eliminating need for junction boxes
- F/O and DC housed in single corrugated cable saves CAPEX by standardizing RRH cable installation and reducing installation equipments



HYBRIFLEX Series

**Technical features**

**STRUCTURE**

<b>Cable Type</b>		4 RRU HYBRIFLEX™ Standard LTE
<b>Size</b>		7/8
<b>Fire Performance</b>		Halogene Free

**MECHANICAL SPECIFICATIONS**

<b>Outer Diameter Nominal</b>	mm (in)	27.8 (1.09)
<b>Cable Weight</b>	kg/m (lb/ft)	0.86 (0.58)
<b>Minimum Bending Radius, Single Bend</b>	mm (in)	120 (4.7)
<b>Minimum Bending Radius, Multi Bends</b>	mm (in)	250 (9.8)
<b>Tensile Strength</b>	N (lb)	700 (157)
<b>Recommended / Maximum Clamp Spacing</b>	m (ft)	0.8 / 1 (2.75 / 3.3)

**DC POWER CABLE SPECIFICATIONS**

Number of DC Pairs		4
Maximum DC-Resistance Power Cable	$\Omega/\text{km}$ ( $\Omega/\text{kft}$ )	3.3 (1)
Cross Section of Power Cable	$\text{mm}^2$ (AWG)	6 (10)
Shielding		provided by aluminium armor
DC Wire Jacket Material		Polyethylene, PE, Metalhydroxite Filling
DC Wire Jacket Thickness	mm (in)	0.5 (0.02)
DC Cable Single Bending Radius	mm (in)	100 (3.94)
DC Cable Diameter	mm (in)	9.9 (0.39)
DC Cable Jacket		UV stable black and blue PE
DC Standards (Meets or Exceeds)		IEC 60228

**CABLE JACKET**

UV-Protection Individual and External Jacket		Yes
Jacket Material		UV stable black PE

**ARMOR SPECIFICATIONS**


Armor Type		Corrugated Aluminum tube
Maximum DC-Resistance of Armor	$\Omega/\text{km}$ ( $\Omega/\text{kft}$ )	1.21 (0.37)
Copper Equivalent Cross Section of Armor	$\text{mm}^2$ (AWG)	16 (5)
Diameter Corrugated Armor	mm (in)	25.2 (0.99)

**F/O CABLE SPECIFICATIONS**

F/O Cable Type		Tight-Buffer, Single mode
Number of F/O Pairs		8
Core/Clad	$\mu\text{m}$	9 /125
Secondary Protection Nominal	$\mu\text{m}$ (in)	900 (0.035)
Single Bending Radius	mm (in)	69 (2.71)
Cable Diameter mm (in)		6.9 (0.27)
F/O Cable Jacket		UV stable black PE
F/O Standards (Meets or Exceeds)		ITU G 657.A2

**TESTING AND ENVIRONMENTAL**

Storage Temperature	$^{\circ}\text{C}$ ( $^{\circ}\text{F}$ )	-40 to 85 (-40 to 185 )
Operation Temperature	$^{\circ}\text{C}$ ( $^{\circ}\text{F}$ )	-40 to 85 (-40 to 185 )
Installation Temperature	$^{\circ}\text{C}$ ( $^{\circ}\text{F}$ )	-20 to 50 (-4 to 122 )
Jacket Specifications		not applicable
LSZH Specification		not applicable



- 1) External Jacket
- 2) Aluminum Armor
- 3) Power Wire
- 4) F/O Cable
- 5) Rip Cord

Product Detail

External Document Links

[Handling Instruction.pdf](#)

[Ordering\\_code.pdf](#)

[Solution Overview\\_4.pdf](#)

[Solution Overview\\_5.pdf](#)

Notes