



HELIFLEX® 1-5/8" low loss air dielectric cable; standard, self-healing jacket

**FEATURES / BENEFITS**

• **Low Attenuation**

The low attenuation of HELIFLEX® coaxial cable results in highly efficient signal transfer in your RF system.

• **Complete Shielding**

The solid outer conductor of HELIFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.

• **Low VSWR**

Special low VSWR versions of HELIFLEX® coaxial cables contribute to low system noise.

• **Outstanding Intermodulation Performance**

HELIFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.

• **High Power Rating**

Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, HELIFLEX® cable provides safe long term operating life at high transmit power levels.

• **Wide Range of Application**

Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.



1-5/8" HELIFLEX® Air Dielectric Coaxial Cable

**Technical features**

**APPLICATIONS**

<b>Applications</b>		Wireless Communication	TV & Radio	HF Defense	Mobile Radio	Cable Solutions
---------------------	--	------------------------	------------	------------	--------------	-----------------

**STRUCTURE**

<b>Size</b>			1-5/8
<b>Jacket Option</b>			Black Self healing
<b>Inner Conductor</b>	mm (in)		18.6 (0.73)
<b>Inner Conductor Material</b>			Corrugated Copper Tube
<b>Dielectric</b>	mm (in)		39.8 (1.56)
<b>Dielectric Material</b>			Helical Polyethylene Spacer
<b>Outer Conductor</b>	mm (in)		46.6 (1.83)
<b>Outer Conductor Material</b>			Corrugated Copper
<b>Jacket</b>	mm (in)		50.4 (1.984)
<b>Jacket Material</b>			Polyethylene, PE, Bitumen Filling
<b>Cable Type</b>			Air-Dielectric, Corrugated

**TESTING AND ENVIRONMENTAL**

<b>Fire Performance</b>			Halogene Free
<b>Installation Temperature</b>	°C(°F)		-25 to 60 (-13 to 140)
<b>Storage Temperature</b>	°C (°F)		-70 to 85 (-94 to 185)
<b>Operation Temperature</b>	°C(°F)		-50 to 85 (-58 to 185)



**ELECTRICAL SPECIFICATIONS**

<b>Impedance</b>	Ω	50 +/- 0.5
<b>Maximum Frequency</b>	GHz	3
<b>Velocity</b>	%	95
<b>Capacitance</b>	pF/m (pF/ft)	70 (21.3)
<b>Inductance</b>	uH/m (uH/ft)	0.175 (0.053)
<b>Peak Power Rating</b>	kW	270
<b>RF Peak Voltage</b>	Volts	5200
<b>Jacket Spark</b>	Volt RMS	8000
<b>Inner Conductor dc Resistance</b>	Ω/1000 m (Ω/1000 ft)	1.06 (0.33)
<b>Outer Conductor dc Resistance</b>	Ω/1000 m (Ω/1000 ft)	0.39 (0.13)
<b>Return Loss (VSWR) Performance</b>		Standard
<b>Min. Return Loss (Max. VSWR)</b>	dB (VSWR)	Typical 20.8dB (1.2 VSWR) or better within the operation bands of most global frequency ranges. Premium also available. Contact factory for options in your specific frequency band.
<b>Phase Stabilized</b>		Phase stabilized and phase matched cables and assemblies are available upon request.
<b>Temperature &amp; Power</b>		Standard

**MECHANICAL SPECIFICATIONS**

<b>Cable Weight, Nominal</b>	kg/m (lb/ft)	1.3 (0.89)
<b>Minimum Bending Radius, Single Bend</b>	mm (in)	180 (7)
<b>Minimum Bending Radius, Repeated Bends</b>	mm (in)	550 (22)
<b>Bending Moment</b>	Nm (lb-ft)	42 (31)
<b>Tensile Strength</b>	N (lb)	1500 (337)
<b>Recommended / Maximum Clamp Spacing</b>	m (ft)	0.8 / 1.2 (2.75 / 4)



**ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)**

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
0.5	0.04	0.01	270
1	0.06	0.02	196
1.5	0.08	0.02	160
2	0.09	0.03	138
10	0.20	0.06	61.40
20	0.28	0.09	43.40
30	0.34	0.10	35.40
50	0.44	0.14	27.30
88	0.59	0.18	20.50
100	0.63	0.19	19.20
108	0.66	0.20	18.40
150	0.78	0.24	15.60
174	0.84	0.26	14.40
200	0.90	0.28	13.50
300	1.11	0.34	11
400	1.29	0.39	9.44
450	1.38	0.42	8.83
500	1.45	0.44	8.41
512	1.47	0.45	8.30
600	1.60	0.49	7.64
700	1.74	0.53	7.03
800	1.86	0.57	6.59
824	1.89	0.58	6.49
894	1.98	0.60	6.20
900	1.98	0.61	6.20
925	2.01	0.61	6.11
960	2.05	0.63	6
1000	2.10	0.64	5.86
1250	2.37	0.72	5.21
1500	2.61	0.80	4.75
1700	2.80	0.85	4.44
1800	2.89	0.88	4.31
2000	3.06	0.93	4.08
2200	3.22	0.98	3.89
2300	3.30	1.01	3.81
3000	3.83	1.17	3.32

External Document Links

Notes