

**HCH-300-1R**Cable hanger for HELIFLEX<sup>®</sup> Air-dielectric coaxial cable

Hangers for the installation of HELIFLEX<sup>®</sup> cables on different supporting profiles.  
Cable Clamp and Extended Counterbed hot-galvanized steel  
Screw: stainless steel.

**FEATURES / BENEFITS**

picture shows the 1L4 version  
for illustration purpose only

**External Document Links****Notes**

Hangers for flat iron 6-12 mm (0.24-0.47")

**Technical features****GENERAL SPECIFICATIONS**

Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Flat iron 6-12mm (0.24-0.47")
Transmission Line Type		HCA300
Cable Type		Air Dielectric

**MECHANICAL SPECIFICATIONS**

Cable Size		3
Material		Cable Clamp : hot-dip galvanized Extended Counterbed : hot-dip galvanized Screw: Stainless steel
Recommended / Maximum Clamp Spacing	m (ft)	0.8 / 1.2 (2.75 / 4)

**TEMPERATURE SPECIFICATIONS**

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185 )

**PACKAGING INFORMATION**

Package Quantity		1
Weight per piece	kg (lb)	0.48 (1.05)