

Hangers for the installation of HELIFLEX[®] cables on different supporting profiles. Cable Clamp and Extended Counterbed hot-galvanized steel Screw: stainless steel. FEATURES / BENEFITS



picture shows the 1L4 version for illustration purpose only

External Document Links

Notes

Hangers for anchor bar 18-22 mm (0.71-0.87")

Technical features

GENERAL SPECIFICATIONS Product Line Coaxial Cable Accessories **Product Type** Hanger Anchor bar 18-22mm (0.71-0.87") Hanger Type **Transmission Line Type** HCA400 Cable Type Air Dielectric **MECHANICAL SPECIFICATIONS** Cable Size 4 Cable Clamp : hot-dip galvanized Material Extended Counterbed : hot-dip galvanized Screw: Stainless steel **Recommended / Maximum** m (ft) 0.8 / 1.2 (2.75 / 4) **Clamp Spacing TEMPERATURE SPECIFICATIONS Operation Temperature** °C (°F) -50 to 85 (-58 to 185) **Storage Temperature** °C (°F) -50 to 85 (-58 to 185) **PACKAGING INFORMATION Package Quantity** 1 Weight per piece 0.75 (1.65) kg (lb)



PRODUCT DATASHEET HCH-400-1C Cable hanger for HELIFLEX[®] Air-dielectric coaxial cable

