



The hoisting grip consists of a wire mesh with 1 hoisting eye, lace up version

**FEATURES / BENEFITS**

**Antenna Transmission Line Installation**

- Hoisting stockings distribute the force during installation
- It holds the antenna transmission line by means of friction over their complete length
- The closed version (C-Type) is used when top connector is installed after the antenna transmission line is hoisted
- The open version (L-Type) is used where the top connector is installed prior to the hoisting



**Technical features**

**STRUCTURE**

|                        |  |   |
|------------------------|--|---|
| Product Line           |  | Coaxial Cable Accessories, Elliptical Waveguide Accessories |
| Product Type           |  | Hoisting Grip   |
| Transmission Line Type |  | LCF78, HCA78, UCF78, EP100, E105, EP105                     |
| Coaxial Cable Type     |  | Air Dielectric, Foam Dielectric                             |
| Configuration          |  | 1 loop attachment   |
| Style                  |  | Lace-Up   |

**MECHANICAL SPECIFICATIONS**

|          |  |                 |
|----------|--|-----------------|
| Material |  | Stainless steel |
|----------|--|-----------------|

**PACKAGING INFORMATION**

|                  |  |   |
|------------------|--|---|
| Package Quantity |  | 1 |
|------------------|--|---|

**External Document Links**

**Notes**