



CELLFLEX® 1-1/4" premium attenuation low loss flexible cable

#### FEATURES / BENEFITS

- **Low Attenuation**

The low attenuation of CELLFLEX® coaxial cable results in highly efficient signal transfer in your RF system.

- **Complete Shielding**

The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.

- **Low VSWR**

Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.

- **Outstanding Intermodulation Performance**

CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.

- **High Power Rating**

Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.

- **Wide Range of Application**

Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

- **Meets/Exceeds:** IEC 60754-1, -2; IEC 60332-1-1; IEC 61034-1, -2; IEC 60332-3-24; [EN50575](#)



1-1/4" CELLFLEX® Low-Loss Foam Dielectric Coaxial Cable

## Technical features

#### APPLICATIONS

Applications		Indoor	Wireless Communication	TV & Radio	HF Defense	Mobile Radio	Cable Solutions
--------------	--	--------	------------------------	------------	------------	--------------	-----------------

#### STRUCTURE

Cable Type		Foam-Dielectric, Corrugated
Size		1-1/4
Jacket Option		Black
Inner Conductor Diameter	mm (in)	13.1 (0.52)
Inner Conductor Material		Copper Tube
Dielectric Diameter	mm (in)	32.7 (1.29)
Dielectric Material		Foam Polyethylene
Outer Conductor Diameter	mm (in)	35.9 (1.41)
Outer Conductor Material		Corrugated Copper
Jacket Diameter	mm (in)	39 (1.54)
Jacket Material		Polyethylene, PE, Metalhydroxite Filling

#### TESTING AND ENVIRONMENTAL

Fire Performance		Flame Retardant, LSOH
Installation Temperature	°C (°F)	-15 to 60 (5 to 140)
Storage Temperature	°C (°F)	-70 to 85 (-94 to 185)
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)

**ELECTRICAL SPECIFICATIONS**

Impedance	Ω	50 +/- 1
Maximum Frequency	GHz	3.7
Velocity	%	89
Capacitance	pF/m (pF/ft)	75 (22.9)
Inductance	uH/m (uH/ft)	0.188 (0.057)
Peak Power Rating	kW	176
RF Peak Voltage	Volts	4200
Jacket Spark	Volt RMS	10000
Inner Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	0.83 (0.25)
Outer Conductor dc Resistance	Ω/1000 m (Ω/1000 ft)	0.73 (0.22)
Return Loss (VSWR) Performance		Standard (for 40-2700, 3300-3700 MHz) or Premium
Min. Return Loss (Max. VSWR)	dB (VSWR)	Standard 20 (1.222), Premium 24 (1.135)/ 23 (1.152)
Phase Stabilized		Phase stabilized and phase matched cables and assemblies are available upon request.
Temperature & Power		Standard

**MECHANICAL SPECIFICATIONS**

Cable Weight, Nominal	kg/m (lb/ft)	0.97 (0.65)
Minimum Bending Radius, Single Bend	mm (in)	200 (8)
Minimum Bending Radius, Repeated Bends	mm (in)	380 (15)
Bending Moment	Nm (lb-ft)	43 (32)
Tensile Strength	N (lb)	2490 (560)
Recommended / Maximum Clamp Spacing	m (ft)	1 / 1.2 (3.25 / 4)

**ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)**

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
100	0.82	0.25	13.50
200	1.17	0.36	9.40
450	1.81	0.55	6.07
700	2.29	0.70	4.80
800	2.47	0.75	4.45
900	2.63	0.80	4.18
1900	4	1.22	2.75
2000	4.12	1.26	2.67
2200	4.35	1.33	2.53
2500	4.69	1.43	2.34
2700	4.90	1.49	2.24
3000	5.21	1.59	2.11
3600	5.80	1.77	1.90
3700	5.90	1.80	1.86



External Document Links

[Web URL to CPR resources with DoP and CE-label download folders](#)

Notes