



CELLFLEX® 1-1/4" premium attenuation low loss flexible cable

#### FEATURES / BENEFITS

- **Ultra Low Attenuation**

The further reduced attenuation of CELLFLEX® premium attenuation coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.

- **Complete Shielding**

The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.

- **Low VSWR**

Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.

- **Outstanding Intermodulation Performance**

CELLFLEX® coaxial cables solid inner and outer conductors virtually eliminate intermods.

Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.

- **High Power Rating**

Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.

- **Wide Range of Application**

Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

- **Meets/Exceeds:** IEC 60754-1, -2; IEC 60332-1-1; IEC 61034-1, -2; IEC 60332-3-24; EN50575



1-1/4" CELLFLEX® Low-Loss Foam Dielectric Coaxial Cable

## Technical features

#### APPLICATIONS

| Applications |  | Indoor | Wireless Communication | TV & Radio | HF Defense | Mobile Radio | Cable Solutions |
|--------------|--|--------|------------------------|------------|------------|--------------|-----------------|
|--------------|--|--------|------------------------|------------|------------|--------------|-----------------|

#### STRUCTURE

|                          |         |  |
|--------------------------|---------|--|
| Cable Type               |         | Foam-Dielectric, Corrugated              |
| Size                     |         | 1-1/4                                    |
| Jacket Option            |         | Black                                    |
| Inner Conductor Diameter | mm (in) | 13.1 (0.52)                              |
| Inner Conductor Material |         | Copper Tube                              |
| Dielectric Diameter      | mm (in) | 32.7 (1.29)                              |
| Dielectric Material      |         | Foam Polyethylene                        |
| Outer Conductor Diameter | mm (in) | 35.9 (1.41)                              |
| Outer Conductor Material |         | Corrugated Copper                        |
| Jacket Diameter          | mm (in) | 39 (1.54)                                |
| Jacket Material          |         | Polyethylene, PE, Metalhydroxite Filling |

#### TESTING AND ENVIRONMENTAL

|                          |         |                        |
|--------------------------|---------|------------------------|
| Fire Performance         |         | Flame Retardant, LS0H  |
| Installation Temperature | °C (°F) | -25 to 60 (-13 to 140) |
| Storage Temperature      | °C (°F) | -70 to 85 (-94 to 185) |
| Operation Temperature    | °C (°F) | -50 to 85 (-58 to 185) |

**ELECTRICAL SPECIFICATIONS**

|                                |                         |  |
|--------------------------------|-------------------------|--|
| Impedance                      | Ω                       | 50 +/- 1   |
| Maximum Frequency              | GHz                     | 3.7  |
| Velocity                       | %                       | 89   |
| Capacitance                    | pF/m (pF/ft)            | 75 (22.9)  |
| Inductance                     | uH/m (uH/ft)            | 0.188 (0.057)  |
| Peak Power Rating              | kW                      | 176  |
| RF Peak Voltage                | Volts                   | 4200   |
| Jacket Spark                   | Volt RMS                | 10000  |
| Inner Conductor dc Resistance  | Ω/1000 m<br>(Ω/1000 ft) | 0.83 (0.25)  |
| Outer Conductor dc Resistance  | Ω/1000 m<br>(Ω/1000 ft) | 0.73 (0.22)  |
| Passive Intermodulation PIM    | typ. dBc                | -160   |
| Return Loss (VSWR) Performance |                         | Standard (for 40-2700, 3300-3700 MHz) or Premium                                     |
| Min. Return Loss (Max. VSWR)   | dB (VSWR)               | Standard 20 (1.222), Premium 24 (1.135)/ 23 (1.152)                                  |
| Phase Stabilized               |                         | Phase stabilized and phase matched cables and assemblies are available upon request. |
| Temperature & Power            |                         | Standard   |

**MECHANICAL SPECIFICATIONS**

|  |              |                    |
|--|--------------|--------------------|
| Cable Weight, Nominal                  | kg/m (lb/ft) | 0.97 (0.65)        |
| Minimum Bending Radius, Single Bend    | mm (in)      | 200 (8)            |
| Minimum Bending Radius, Repeated Bends | mm (in)      | 380 (15)           |
| Bending Moment                         | Nm (lb-ft)   | 43 (32)            |
| Tensile Strength                       | N (lb)       | 2490 (560)         |
| Recommended / Maximum Clamp Spacing    | m (ft)       | 1 / 1.2 (3.25 / 4) |



ATTENUATION @ 20°C (68°F) AND POWER RATING @ 40°C (104°F)

| Frequency, MHz | dB per 100m | dB per 100ft | Power, kW |
|----------------|-------------|--------------|-----------|
| 100            | 0.82        | 0.25         | 13.50     |
| 200            | 1.17        | 0.36         | 9.40      |
| 450            | 1.81        | 0.55         | 6.07      |
| 700            | 2.29        | 0.70         | 4.80      |
| 800            | 2.47        | 0.75         | 4.45      |
| 900            | 2.63        | 0.80         | 4.18      |
| 1900           | 4           | 1.22         | 2.75      |
| 2000           | 4.12        | 1.26         | 2.67      |
| 2200           | 4.35        | 1.33         | 2.53      |
| 2500           | 4.69        | 1.43         | 2.34      |
| 2700           | 4.90        | 1.49         | 2.24      |
| 3000           | 5.21        | 1.59         | 2.11      |
| 3300           | 5.51        | 1.68         | 2         |
| 3700           | 5.90        | 1.80         | 1.86      |

External Document Links

Notes