




Coaxial Adapter N male - female

FEATURES / BENEFITS



Technical features

STRUCTURE

| | | |
|--------------|--|--------------------------|
| Product Line | | Coaxial Cable Components |
| Product Type | | Coaxial Adapter |

MECHANICAL SPECIFICATIONS

| | | |
|----------------------------|--|------------------------------|
| Connector A | | N Male |
| Center Contact Connector A | | Brass, silver plated |
| Outer Contact Connector A | | Brass, CuSnZn plated |
| Connector B | | N Female |
| Center Contact Connector B | | Spring Bronze, Silver plated |
| Outer Contact Connector B | | Brass, CuSnZn plated |
| Dielectric | | PTFE |
| Sealing class | | IP68, connected |

ELECTRICAL SPECIFICATIONS

| | | |
|-----------------------------------|-----------|---|
| Frequency Range - MHz | | DC - 6000 |
| VSWR, Return Loss | VSWR (dB) | 0-3000 MHz: 1.06 (30.71) 3000-6000 MHz: 1.10 (26.44) |
| Insertion Loss, dB (Max) | dB | 0.1 |
| 3rd Order IM Product @ 2x20 Watts | dBc | -163 |
| Power Rating | kW | 0.5 |

TEMPERATURE SPECIFICATIONS

| | | |
|-----------------------|---------|------------------------|
| Operation Temperature | °C (°F) | -45 to 85 (-49 to 185) |
|-----------------------|---------|------------------------|

PACKAGING INFORMATION

| | | |
|------------------|--|---|
| Package Quantity | | 1 |
|------------------|--|---|

External Document Links

Notes