

PRODUCT DATASHEET NM-RA78-015 N Male Connector for 7/8" RADIAFLEX® cable

These single-piece high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to RADIAFLEX® cables. The connectors provide outstanding value to users because they permit quick, easy and reliable installation at any location, thereby allowing the operator flexibility while saving installation time and money. They attach to prepared cable in one piece assuring error-free attachment. All connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in both type N and 7-16 DIN interface.

FEATURES / BENEFITS

- Single-piece design for Fast and Easy Installation Reliable and simple attachment avoids unnecessary connector adjustments and provides outstanding performance. Saves time and provides cost savings.
- Robust Mechanical Design Low and consistent IM performance.
- Excellent Electrical Performance Low VSWR
- Totally Waterproof Assures safe, long term operation in the harshest of environments.
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



RADIAFLEX connector

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable	
Cable Size		7/8	
Cable Type		Radiating	
Model Series		all RLF, RLK and RAY78-50A-Series	
Connector Interface		Ν	
Connector Type		Straight	
Sealing Method		Shrinking Sleeve	
Gender		Male	
ELECTRICAL SPECIFICATIONS			
Nominal Impedance, ohms	Ohm	50	
Maximum Frequency	GHz	3.7	
VSWR, Return Loss	VSWR (dB)	0 - 1 GHz: 1.03 (36.6) 1 - 2,7 GHz: 1.06 (30.7) 2,7 - 3,7 GHz: 1.08 (28.3)	
MECHANICAL SPECIFICATIONS			
Length	mm (in)	78.4 (3.09)	


Length	mm (in)	78.4 (3.09)	
Outer Diameter	mm (in)	34 (1.33)	
Body Material		Brass / Plating: Tri metal	
Inner Contact Material		Copper / Plating: Silver	
Inner Contact Attachment		Spring Finger / Plating: silver	
Outer Contact Attachment		Spring loop / Plating: silver	
TESTING AND ENVIRONMENTAL			
Waterproof Level		IP68	

NM-RA78-015

REV : E

REV DATE : 29 Oct 2024





External Document Links Application Note Installation Instruction

Notes