Fiber Distribution Box, including SC/APC adapters, indoor/outdoor, up to 96 fibers, steel

RFS' HYBRIFLEX ™ The optical splitter cable distribution box is for indoor Distributed Radio System. It is monted at wall ,pole or ceiling and acts as an interface between fiber riser cable and fiber jumper to Radio. Splice protection sleeve is included.

FEATURES / BENEFITS

- Provides interconnection for F/O trunk riser and branch or jumper F/O cable.
- Cassette splitter pre-terminated in factory, 100% tested to ensure the transmission performance
- Built-in stacked splice tray, easy for open, the splice tray can be taken down, easy for installation and maintenance.
- SC/APC F/O adapters modular design, convenient for fixing and maintenance
- The box door opening Angle is >120°, easy for handling cables and connections inside box



External Document Links Notes

Technical features

GENERAL SPECIFICATIONS

| Product Type | Hybriflex |
|--------------|-----------|
| | |

MECHANICAL SPECIFICATIONS

| Material | sheet metal |
|----------|---|
| Mounting | Wall mounted, pole, aerial installation |

TESTING AND ENVIRONMENTAL

| Storage Temperature | °C (°F) | -40 to 65 (-40 to 149) | | |
|-----------------------|---------|-------------------------|--|--|
| Operation Temperature | °C (°F) | -40 to 65 (-40 to 149) | | |

CABLES SUPPORTED

| Supported F/O Connections | SC / APC |
|-----------------------------|----------|
| Supported 170 confidentions | 3677116 |

ADDITIONAL INFORMATION

| | SBIF-0Z06SS-APCM- YC | SBIF-0Z12SS-APCM- YC | SBIF-0Z24SS-APCM- YC | SBIF-0Z36SS-APCM- YC | SBIF-0Z48SS-APCM- YC |
|----------------------------------|---|---|---|---|---|
| Outer Diameter | 380 mm × 350 mm × 90 mm | 380 mm × 350 mm × 90 mm | 380 mm × 350 mm × 120 mm | 550 mm × 450 mm × 120 mm | 550 mm × 450 mm × 130 mm |
| Quantity of Pigtails included | 0 | 0 | 0 | 0 | 0 |
| Splitter and Adapter Ports | 12 | 24 | 36 | 48 | 96 |
| Insertion loss (adapter&pigtail) | ≤ 0.3dB |
| Return loss (SC/APC) | ≥ 60dB |
| Operation Humidity | ≤95% 30 no corrosive gases around |
| Atmospheric pressure | 70Кра 106Кра |

SBIF-0ZXXSS-APCM-YC REV : A REV DATE : 17 Jan 2022 www.rfsworld.com

Fiber Distribution Box, including SC/APC adapters, indoor/outdoor, up to 96 fibers, steel



Example for 96 pairs

SBIF-OZXXSS-APCM-YC REV : A REV DATE : 17 Jan 2022 www.rfsworld.com