

**RFS' HYBRIFLEX™** Optical Fibre Cable Distribution Terminal Box for Indoor 12/24 Cores**FEATURES / BENEFITS**

- High quality plastic material (ABS+PC), Excellent mechanical strength, Elegant appearance, sturdiness and durability
- Indoor Wall&Pole-mounted installation
- Space and fixing devices are reserved for fiber cable, pigtail and grounding inside the box
- Pigtail fastened by high end elastomer and fixed reliably and conveniently
- Built-in stacked splice tray, easy for open, the splice tray can be taken down, easy for installation and maintenance.
- Fibre routing reasonable, bending radius of fibres in any place is greater than 30mm

**External Document Links****Notes****Technical features****GENERAL SPECIFICATIONS**

| | | |
|--------------|--|-----------|
| Product Type | | Hybriflex |
|--------------|--|-----------|

MECHANICAL SPECIFICATIONS

| | | |
|----------|--|----------|
| Material | | PC + ABS |
|----------|--|----------|

TESTING AND ENVIRONMENTAL

| | | |
|--------------------------|---------|------------------------|
| Storage Temperature | °C (°F) | -20 to 60 (-4 to 140) |
| Operation Temperature | °C (°F) | -20 to 60 (-4 to 140) |
| Installation Temperature | °C (°F) | -20 to 60 (-4 to 140) |

CABLES SUPPORTED

| | | |
|---------------------------|--|---------------------------------|
| Supported F/O Connections | | 12-24 splicer cassette capacity |
|---------------------------|--|---------------------------------|

FAMILY INFORMATION

| | | |
|--|-------------------------|-------------------------|
| | SBIF-0Z06Z-OS-YC | SBIF-0Z12Z-OS-YC |
| Outer Diameter | 290 mm × 175 mm × 82 mm | 290 mm × 175 mm × 82 mm |
| Capacity of Cores | 12 | 24 |
| Quantity of Splice Protection Sleeves included | 20 | 30 |