



\* Cable tie for installation of RADIAFLEX<sup>®</sup> cable to external messenger wire. Suitable for all sizes of RADIAFLEX<sup>®</sup> cable. Tool TAS-TOOL-01 can be used for professional adjustment of the plastic cable tie.

**FEATURES / BENEFITS**

- No influence on the electrical transmission characteristics of the RADIAFLEX<sup>®</sup> radiating cable
- Robust mechanical design
- UV resistant
- Halogen-free



TAS-120L

**Technical features****STRUCTURE**

Product Line		Radiating Cable Accessories
Product Type		Installation Hardware
Transmission Line Type		Radiating Cables (all sizes)
Coaxial Cable Type		Foam Dielectric Radiating Cable
Cable Size		1/2", 7/8", 1 1/4", 1 5/8"

**ACCESSORIES**

Required Tool		: TAS-TOOL-01
---------------	--	---------------

**MECHANICAL SPECIFICATIONS**

Color		Black
Material		Polyamide 6.6 High Imp. Mod., Heat Stab. (PA66HIRHSUV), Polypropylene, UV-resistant (PPW)

**TESTING AND ENVIRONMENTAL**

Fire Class		UL94 HB
------------	--	---------

**TEMPERATURE SPECIFICATIONS**

Installation Temperature	°C (°F)	0 to 50 (32 to 122 )
Operation Temperature	°C (°F)	-20 to 85 (-4 to 185 )
Storage Temperature	°C (°F)	-20 to 85 (-4 to 185 )

**PACKAGING INFORMATION**

Package Quantity		25
------------------	--	----

**External Document Links****Notes**

- For an installation between 0° to 10° Celsius (32°-50° F), the installation tool TAS-TOOL-01 is strictly required.
- For an installation above 10° Celsius (50° F), the tool TAS-TOOL-01 is strongly recommended.
- An installation below 0° Celsius (32° F) is not allowed.