



Twistable and flexible rectangular waveguide R320, with PBR/PBR 320 flanges. Length = 0.6m, core with environmental impact resistant molded rubber jacket. Hardware and gasket (for PDR/PBR flanges) included.

FEATURES / BENEFITS

Waveguide installation

- The flexible and twistable rectangular waveguide component eliminates installation difficulties
- It isolates vibration
- It provides simple aid to positioning of antennas

**Technical features****STRUCTURE**

Type of Rectangular Waveguide Component		TwistFlex
Waveguide Size IEC (EIA)		R320 (WR28)
Flange A		PBR320
Flange B		PBR320
Flange Finish		Brass un-plated
Package Quantity		1

ELECTRICAL SPECIFICATIONS

Frequency Range	GHz	26.4 - 40.1
Minimum Return Loss (max. VSWR)	dB (VSWR)	19.7 (1.23)
Attenuation	dB	1.2
Power rating	W	75

MECHANICAL SPECIFICATIONS

Maximum Twist	degree/m (degree/ft)	360 (109.7)
Minimum Bending Radius E-Plane	mm (in)	22 (0.9)
Minimum Bending Radius H-Plane	mm (in)	40 (1.6)
Length	mm (in)	600 (23.6)
Weight	kg (lb)	0.15 (0.33)

MATERIAL

Material		Core: Brass silver plated Jacket: Rubber Silicone Flange: Brass
Color		Black

External Document Links

[AN 030707-8 Application note for RFS Twistflex](#)

Notes