



Twistable and flexible rectangular waveguide R320, with PBR/UBR 320 flanges. Length = 0.9m, core with environmental impact resistant molded rubber jacket. Hardware and gasket (for PDR/PBR flanges) included.



FEATURES / BENEFITS

Waveguide installation

- The flexible and twistable rectangular waveguide component eliminates installation difficulties
- It isolates vibration
- It provides simple aid to positioning of antennas

Technical features

STRUCTURE

| | | |
|---|--|-----------------|
| Type of Rectangular Waveguide Component | | TwistFlex |
| Waveguide Size IEC (EIA) | | R320 (WR28) |
| Flange A | | PBR320 |
| Flange B | | UBR320 |
| Flange Finish | | Brass un-plated |
| Package Quantity | | 1 |

ELECTRICAL SPECIFICATIONS

| | | |
|---------------------------------|-----------|-------------|
| Frequency Range | GHz | 26.5 - 40 |
| Minimum Return Loss (max. VSWR) | dB (VSWR) | 17.7 (1.30) |
| Attenuation | dB | 1.8 |
| Power rating | W | 75 |

MECHANICAL SPECIFICATIONS

| | | |
|--------------------------------|----------------------|-------------|
| Maximum Twist | degree/m (degree/ft) | 360 (109.7) |
| Minimum Bending Radius E-Plane | mm (in) | 25 (1) |
| Minimum Bending Radius H-Plane | mm (in) | 50 (2) |
| Length | mm (in) | 900 (35.4) |

MATERIAL

| | | |
|----------|--|--|
| Material | | Core: Brass silver plated Jacket: Vulcanised Neoprene Rubber Flange: Brass |
| Color | | Black |

External Document Links

[AN 030707-8 Application note for RFS Twistflex](#)

Notes